

Title (en)
Roller latch bolt with bolt shaft

Title (de)
Rollfalle mit einem Rollfallenschaft

Title (fr)
Pêne demi-tour à rouleau avec une tige arrière

Publication
EP 0785321 B1 20030416 (DE)

Application
EP 97890008 A 19970117

Priority
AT 9396 A 19960119

Abstract (en)
[origin: EP0785321A1] The roller latch can be pushed outwards up to a stop and its shaft has a releasable connection with the latch lever. The shaft (7) supports an adjustable stop (9), which in its operating position, viewed in the movement direction of the shaft, extends over the periphery of the cover opening for the latch. An actuator (11) is provided for pushing in or pivoting inwards the stop on the face side to the latch (8) for removal and possibly for exchange against a wedge latch. The stop, by pressing in the operating component against spring force, can be released from a positive engagement connection and is accordingly rotatable out of the function position in the peripheral area of the cover opening for the roller latch.

IPC 1-7
E05B 15/10; **E05B 63/22**

IPC 8 full level
E05B 15/10 (2006.01); **E05B 63/22** (2006.01); **E05B 63/06** (2006.01)

CPC (source: EP)
E05B 15/102 (2013.01); **E05B 63/0056** (2013.01); **E05B 63/044** (2013.01); **E05B 63/22** (2013.01); **E05B 63/06** (2013.01)

Cited by
EP1522660A3; EP0987387A3; CN108071631A; EP0940532A3; EP1088955A3; US6663147B1; EP2243910A2; WO2012011134A1

Designated contracting state (EPC)
DE FR GB IT

DOCDB simple family (publication)
EP 0785321 A1 19970723; **EP 0785321 B1 20030416**; AT 405551 B 19990927; AT A9396 A 19990115; DE 59709810 D1 20030522

DOCDB simple family (application)
EP 97890008 A 19970117; AT 9396 A 19960119; DE 59709810 T 19970117