

Publication

EP 0787873 A3 19970917 (FR)

Application

EP 97101620 A 19970203

Priority

DE 29601885 U 19960205

Abstract (en)

[origin: EP0787873A2] The closing strip has at least one recess (20) for a bolt or other closure element (14). The recess is associated with a guide (30) which has an opening (31) matching the cross-section of the closure element. The guide can be fixed on the strip relative to the recess in different positions which positions the opening differently. The guide can be a turn-over plate having an off-centre opening and the plate may be punched out of sheet metal. The guide can be trough-shaped with the trough edges being of different width.

IPC 1-7

E05B 15/02

IPC 8 full level

E05B 15/02 (2006.01)

CPC (source: EP)

E05B 15/0245 (2013.01)

Citation (search report)

- [X] EP 0539908 A1 19930505 - SCHUERING FENSTERTECH [DE]
- [X] US 4453752 A 19840612 - MCKANN H SMITH [US]
- [A] DE 2445834 A1 19760415 - GRESCHBACH STAHLBAU

Cited by

DE102016113799B3

Designated contracting state (EPC)

AT BE CH DE ES FR GB IT LI NL

DOCDB simple family (publication)

EP 0787873 A2 19970806; EP 0787873 A3 19970917; EP 0787873 B1 20000517; AT E193081 T1 20000615; DE 29601885 U1 19970605; DE 59701677 D1 20000621

DOCDB simple family (application)

EP 97101620 A 19970203; AT 97101620 T 19970203; DE 29601885 U 19960205; DE 59701677 T 19970203