

Title (en)
EXCAVATION REGION SETTING APPARATUS FOR CONTROLLING REGION LIMITED EXCAVATION BY CONSTRUCTION MACHINE

Title (de)
BAGGERBEREICH-FESTLEGUNGSGERÄT ZUR STEUERUNG DER ARBEITSBEREICHSBEGRENZUNG DES BAGGERNS FÜR EINE BAUMASCHINE

Title (fr)
APPAREIL DE DEFINITION D'UNE ZONE A EXCAVER PERMETTANT DE CONTROLER L'EXCAVATION D'UNE ZONE LIMITEE PAR UNE MACHINE DE CONSTRUCTION

Publication
EP 0790355 A4 19990915 (EN)

Application
EP 96926605 A 19960808

Priority

- JP 9602251 W 19960808
- JP 20702395 A 19950814

Abstract (en)
[origin: WO9707296A1] In an excavation region setting apparatus for controlling the region limited excavation by a construction machine, which is adapted to calculate a target speed vector V_c for use in controlling a front unit (1A), on the basis of a vehicle body (1B), restrict when the front unit approaches a boundary of a preset excavation region the moving speed thereof in the direction approaching the same boundary, by correcting the target speed vector, and move the front unit along the mentioned boundary, an outer reference 80 is set first in the horizontal direction in a position outside a hydraulic shovel body, and a depth h_r between the outer reference and the boundary of the excavation region is then set by using a setter (7), for the purpose of setting the excavation region. The front unit (1A) is then moved, and, when the position of a front reference 70 agrees with that of the outer reference, an outer reference setting switch (71) is pressed. Consequently, a control unit (9) computes a height h_f between a vehicle body reference point O and the outer reference, and then a height h_s of a boundary surface of the excavation region with respect to the vehicle body reference point O on the basis of this depth h_r by using the height h_f as a correction value, and set the excavation region based on the vehicle body (1B), on the basis of which the target speed vector V_c is calculated. This enables the setting of an excavation region suitable for an excavation control operation in which computation is carried out on the basis of the vehicle reference to be done, and a highly reliable control operation to be carried out.

IPC 1-7
E02F 3/43

IPC 8 full level
E02F 3/43 (2006.01); **E02F 9/20** (2006.01); **E02F 9/26** (2006.01); **G01C 5/00** (2006.01); **G01C 15/00** (2006.01); **E02F 3/42** (2006.01); **E02F 9/22** (2006.01)

CPC (source: EP KR)
E02F 3/32 (2013.01 - EP); **E02F 3/437** (2013.01 - EP); **E02F 9/20** (2013.01 - KR); **E02F 9/2285** (2013.01 - EP); **E02F 9/2296** (2013.01 - EP); **E02F 9/26** (2013.01 - EP)

Citation (search report)

- [YD] US 4829418 A 19890509 - NIELSEN EDWARD G [US], et al
- [Y] GB 2272204 A 19940511 - KUBOTA KK [JP]
- [PX] EP 0707118 A1 19960417 - HITACHI CONSTRUCTION MACHINERY [JP]
- [E] EP 0735202 A1 19961002 - LASER ALIGNMENT [US]
- [A] WO 9323628 A1 19931125 - KOMATSU MFG CO LTD [JP], et al & US 5490081 A 19960206 - KUROMOTO KAZUNORI [JP], et al
- See references of WO 9707296A1

Cited by
US11377813B2; EP3992371A4; CN113302359A; CN102575455A; US9540793B2; US12000108B2; WO02059428A1; US12091833B2

Designated contracting state (EPC)
DE GB IT

DOCDB simple family (publication)
WO 9707296 A1 19970227; CN 1064426 C 20010411; CN 1157020 A 19970813; DE 69636494 D1 20061012; DE 69636494 T2 20070215; EP 0790355 A1 19970820; EP 0790355 A4 19990915; EP 0790355 B1 20060830; JP 3609164 B2 20050112; JP H0953253 A 19970225; KR 100191392 B1 19990615; KR 970705678 A 19971009

DOCDB simple family (application)
JP 9602251 W 19960808; CN 96190690 A 19960808; DE 69636494 T 19960808; EP 96926605 A 19960808; JP 20702395 A 19950814; KR 19970701094 A 19970220