

Title (en)  
PRINTING PROCESS

Title (de)  
DRUCKVERFAHREN

Title (fr)  
PROCEDE D'IMPRESSION

Publication  
**EP 0790893 B1 19980812 (DE)**

Application  
**EP 95935809 A 19951021**

Priority  
• DE 9501486 W 19951021  
• DE 4439007 A 19941102

Abstract (en)  
[origin: WO9614211A1] It is proposed that the known heat-set printing process for planographic and relief printing should be improved by the use of a short ink mechanism with an engraved roller and ink-scraping device and a printing ink which is solid at room temperature and can be liquefied by heating, and by ensuring that the ink-scraping unit and ink-conducting components of the printing system are set to a temperature above the liquefaction temperature of the printing ink. This prevents the production of waste gas and eliminates the danger of harmful and/or explosive vapour/air mixtures; obviates the need for facilities for drying the ink and processing the waste gases; and reduces energy consumption and the emission of carbon dioxide, heat and combustion by-products.

IPC 1-7  
**B41F 31/00**

IPC 8 full level  
**B41F 31/00** (2006.01)

CPC (source: EP)  
**B41F 31/002** (2013.01)

Citation (examination)  
FLEXOGRAPHIC PRINTING: "ENCYCLOPEDIA OF SCIENCE & TECHNOLOGY; Band 14; Seiten 301 und 302", GRAW-HILL

Designated contracting state (EPC)  
AT BE CH DE ES FR GB IT LI NL

DOCDB simple family (publication)  
**WO 9614211 A1 19960517**; AT E169561 T1 19980815; DE 4439007 A1 19960509; DE 4439007 C2 19970430; DE 59503206 D1 19980917; EP 0790893 A1 19970827; EP 0790893 B1 19980812; ES 2121422 T3 19981116

DOCDB simple family (application)  
**DE 9501486 W 19951021**; AT 95935809 T 19951021; DE 4439007 A 19941102; DE 59503206 T 19951021; EP 95935809 A 19951021; ES 95935809 T 19951021