

Title (en)

Process and device for controlling the flow of a fluidised powder from a container

Title (de)

Verfahren und Einrichtung zur Steuerung des Austritts eines fluidisierten Feststoffes aus einem Behälter

Title (fr)

Procédé et dispositif pour commander l'alimentation d'une poudre fluidisée à partir d'un réservoir

Publication

EP 0792694 B1 20030312 (DE)

Application

EP 97102463 A 19970215

Priority

DE 19606214 A 19960220

Abstract (en)

[origin: US5800876A] A method and a device for controlling the outflow of fluid powder from a container can be used for controlling the expulsion of powder out of a powder-spraying apparatus for electrostatic coating. The disadvantages of a mechanical closing device are avoided by introducing closing air into an extraction pipe for extracting fluidized powder out of a container. The closing air is introduced through a pipe which opens into an orifice in the casing of the extraction pipe. The mass flow of fluidized powder can be controlled by an appropriate setting of a pressure in the extraction pipe in relation to the pressure in the fluid bed, that is to say by the introduction of closing air at an appropriate pressure.

IPC 1-7

B05B 7/14; **B05B 5/03**; **B05B 5/16**

IPC 8 full level

B05D 1/02 (2006.01); **B05B 5/025** (2006.01); **B05B 5/03** (2006.01); **B05B 5/08** (2006.01); **B05B 5/16** (2006.01); **B05B 7/14** (2006.01)

CPC (source: EP KR US)

B05B 5/032 (2013.01 - EP KR US); **B05B 5/1683** (2013.01 - EP KR US); **B05B 5/1691** (2013.01 - EP KR US);
B05B 7/1413 (2013.01 - EP KR US); **Y10S 118/05** (2013.01 - EP US)

Cited by

DE102004013153A1

Designated contracting state (EPC)

AT BE CH DE DK ES FI FR GB IT LI NL SE

DOCDB simple family (publication)

US 5800876 A 19980901; AT E234159 T1 20030315; DE 19606214 A1 19970821; DE 19606214 B4 20060601; DE 59709463 D1 20030417;
EP 0792694 A2 19970903; EP 0792694 A3 19980527; EP 0792694 B1 20030312; JP 3987152 B2 20071003; JP H09313992 A 19971209;
KR 970061773 A 19970912

DOCDB simple family (application)

US 80412997 A 19970220; AT 97102463 T 19970215; DE 19606214 A 19960220; DE 59709463 T 19970215; EP 97102463 A 19970215;
JP 3513797 A 19970219; KR 19970004979 A 19970219