

Title (en)
Article of footwear comprising two detachable elements

Title (de)
Schuhwerk aus zwei trennbaren Elementen

Title (fr)
Ensemble chaussant continué de deux éléments détachables

Publication
EP 0796571 A1 19970924 (FR)

Application
EP 97102276 A 19970213

Priority
FR 9603565 A 19960318

Abstract (en)
The boot consists of two sections - a rigid outer shell (3) fixed to the roller frame (4), and an inner liner (2) or soft boot which fits into the shell. The liner and shell are fixed together by straps (10) which are stitched to the sides of the liner and pass through slots (11) in the sides of the shell. After passing through the shell slots, the straps are taken up over the surface of the shell and fixed in place by a bootlace threaded through holes (7, 7A) in the liner and the ends of the straps. An additional strap round the top of the boot can have a self-adhesive fastening.

Abstract (fr)
Ensemble chaussant pour la pratique du sport, notamment chaussure de patin à roues en ligne, du type comprenant deux éléments (2 et 3), dont l'un interne (2) relativement souple forme un chausson ou chaussure amovible, et l'autre externe (3) relativement rigide comporte une coque, munie d'une ouverture longitudinale (5) à sa partie supérieure pour permettre l'introduction du chausson ou chaussure (2) dans ladite coque (3), puis son serrage sur le pied, par l'intermédiaire d'un lacet (9) reliant entre eux les bords interne (5A) et externe (5B) de ladite ouverture (5), lequel lacet (9) est également apte à coopérer simultanément avec la coque (3) rigide, par l'intermédiaire de moyens de liaison, caractérisé en ce que les moyens de liaison du chausson ou chaussure (2) avec la coque (3) sont constitués par au moins une sangle (10) issue chacune des zones latérales du chausson ou chaussure (2) duquel elle est solidaire et positionnée en regard de moyens de passage correspondants (11) ménagés également sur chacune des parties latérales de la coque rigide (3), la longueur de chacune des sangles (10) étant prévue de façon à pouvoir chevaucher extérieurement les côtés latéraux de la coque (3) et au moins une partie supérieure du chausson ou chaussure (2), avec laquelle elle est reliée par l'intermédiaire du lacet (9) coopérant en traction avec l'extrémité libre (10a) de chacune desdites sangles (10). <IMAGE>

IPC 1-7
A43B 5/16

IPC 8 full level
A43B 5/16 (2006.01); **A43B 7/14** (2006.01); **A43C 1/00** (2006.01)

CPC (source: EP US)
A43B 5/16 (2013.01 - EP US); **A43B 7/1495** (2013.01 - EP US); **A43C 1/00** (2013.01 - EP US)

Citation (search report)
• [A] DE 1191717 B 19650422 - FRANZ FESL
• [A] FR 2668072 A1 19920424 - VULLIERME INTERNATIONAL SARL [FR]
• [A] US 5357695 A 19941025 - LU JINNY [TW]
• [A] US 4282659 A 19810811 - BOURQUE RENE, et al
• [A] US 2096677 A 19371019 - FASSETT LORENZO J

Cited by
FR2772243A1; EP0919265A3; WO9930586A1; WO9837782A1

Designated contracting state (EPC)
AT CH DE FR IT LI

DOCDB simple family (publication)
EP 0796571 A1 19970924; CA 2197397 A1 19970919; FR 2745989 A1 19970919; FR 2745989 B1 19980507; US 5933987 A 19990810; US 6082028 A 20000704

DOCDB simple family (application)
EP 97102276 A 19970213; CA 2197397 A 19970212; FR 9603565 A 19960318; US 29890099 A 19990426; US 8399498 A 19980526