

Title (en)
Perfected burner for heat generator

Title (de)
Verbesserter Brenner für Wärmegenerator

Title (fr)
Brûleur amélioré pour générateur de chaleur

Publication
EP 0797047 A1 19970924 (EN)

Application
EP 97104380 A 19970314

Priority
IT UD960036 A 19960322

Abstract (en)
Perfected burner for heat generators, which can be used in cooperation with heating plants such as boilers, hot air generators etc. for heating rooms in general, the burner comprising at least a containing structure (11) associated with the outer wall of a combustion chamber (26) and defining inside at least the seating for a flame pipe (17) and a ventilator unit (13), the flame pipe (17) containing inside itself a fuel feed pipe (22) and having at its periphery a slit (33) for air to pass through associated with the ventilator unit (13), the ventilator unit (13) having an air propellor (40) carried by an actuating motor (37) supported by a mounting flange (53), the slit (33) cooperating with a shutter (34) element, the fuel feed pipe (22) having at its end a nozzle-type outlet (30) cooperating with a turbulence disk (31), there also being present an intake opening (15), the containing structure (11) defining, at the side of the air propellor, an area (48) through which the air passes and which becomes progressively wider until it reaches a width at least 30% of the diameter of the air propellor (40) in the area substantially diametric to its initial part, and around the flame pipe (17) an annular recircling conduit (45) communicating at its inlet with this area (48) and the air propellor (40) defining inside itself a housing area for at least part of the motor (37), between the motor (37) and the inner diameter of the air propellor (40) there being longitudinal fins (41,42) substantially diametrically arranged and defining, together with the air propellor (40), a lower intake area (44) communicating with the opening (15) and a higher intake area (43) communicating with the annular recircling conduit (45), between the air propellor (40) and the inner side of the containing structure (11) on the side of the flange (53) there being an annular space (54) to convey the air. <IMAGE>

IPC 1-7
F23D 11/00; **F23D 14/36**; **F04D 25/16**

IPC 8 full level
F04D 25/16 (2006.01); **F23D 11/00** (2006.01); **F23D 14/36** (2006.01)

CPC (source: EP)
F04D 25/166 (2013.01); **F23D 11/001** (2013.01); **F23D 14/36** (2013.01)

Citation (search report)

- [YD] FR 2211106 A5 19740712 - FRITSCH HEINRICH [DE]
- [YD] DE 4232178 C1 19931223 - SCHILLING SIEGFRIED W [CH]
- [A] DE 9303936 U1 19930519
- [A] WO 8401809 A1 19840510 - VAILLANT JOH GMBH & CO [DE]
- [A] EP 0295157 A1 19881214 - AIRELEC IND [FR]
- [A] FR 2212864 A5 19740726 - CHAUFFAGE AUTOMATIQUE [FR]
- [A] FR 1573999 A 19690711

Cited by
EP2282117A3; US8882491B2

Designated contracting state (EPC)
AT BE CH DE DK ES FR GB IE IT LI NL PT SE

DOCDB simple family (publication)
EP 0797047 A1 19970924; **EP 0797047 B1 20010919**; AT E205930 T1 20011015; DE 69706731 D1 20011025; DE 69706731 T2 20020508; ES 2163677 T3 20020201; IT 1288866 B1 19980925; IT UD960036 A0 19960322; IT UD960036 A1 19970922

DOCDB simple family (application)
EP 97104380 A 19970314; AT 97104380 T 19970314; DE 69706731 T 19970314; ES 97104380 T 19970314; IT UD960036 A 19960322