

Title (en)

WAX HYDROISOMERIZATION PROCESS

Title (de)

HYDROISOMERISATIONSPROZESS VON WACHSEN

Title (fr)

PROCEDE D'HYDROISOMERISATION DE CIRES

Publication

**EP 0799082 A1 19971008 (EN)**

Application

**EP 95941486 A 19951202**

Priority

- US 9515461 W 19951202
- US 35850494 A 19941219

Abstract (en)

[origin: WO9626993A1] This invention discloses a process for producing a high Viscosity Index lubricant having a VI of at least 125 from a waxy hydrocarbon feed having a wax content of at least 40 wt.%. The process comprises catalytically dewaxing waxy paraffins present in the feed by isomerization in the presence of hydrogen and in the presence of a low acidity large pore zeolite isomerization catalyst. This catalyst has a ratio of SiO<sub>2</sub>/Al<sub>2</sub>O<sub>3</sub>, as synthesized, of at least 200:1, wherein the catalyst is prepared in the absence of boron. The feed may be hydrocracked prior to dewaxing with the large pore zeolite. The effluent of the process may also be further dewaxed by either solvent or catalytic means in order to achieve target pour point.

IPC 1-7

**B01B 1/00**

IPC 8 full level

**C10G 45/64** (2006.01); **C10G 47/12** (2006.01); **C10G 49/02** (2006.01); **C10G 65/02** (2006.01); **C10G 65/04** (2006.01); **C10G 65/12** (2006.01); **C10G 67/04** (2006.01); **C10G 71/00** (2006.01); **C10G 73/06** (2006.01); **C10G 73/44** (2006.01)

CPC (source: EP)

**C10G 45/64** (2013.01)

Designated contracting state (EPC)

BE DE ES FR GB IT NL

DOCDB simple family (publication)

**WO 9626993 A1 19960906**; AU 4289196 A 19960918; AU 706864 B2 19990624; CA 2204127 A1 19960906; EP 0799082 A1 19971008; EP 0799082 A4 19981230; JP H10511425 A 19981104

DOCDB simple family (application)

**US 9515461 W 19951202**; AU 4289196 A 19951202; CA 2204127 A 19951202; EP 95941486 A 19951202; JP 52310396 A 19951202