

Publication

EP 0800848 A3 19971112

Application

EP 97102076 A 19970210

Priority

DE 19609978 A 19960314

Abstract (en)

[origin: EP0800848A2] The horizontal bar axis (6) at its end (7) is rotatably located around a bearing pin (8) in a horizontal plane. The swing body (1) has a running wheel (5). The bar axis connected to the swing body is made of rotary-elastic material or rotary-elastic components and accommodates movements of the swing body and at the same time through a driver (10) located in the swing body transmits the force from a movement direction to the running wheel. The bar axis in the centre of the circulating surface (9) is horizontally pivotably connected at right-angles to its longitudinal axis by bearing components (8). The rotary-elastic bar axis also forms the axis of the running wheel and the foot rests (31,32).

IPC 1-7

A63G 1/20

IPC 8 full level

A47D 13/10 (2006.01); **A63G 1/20** (2006.01); **A63G 19/12** (2006.01)

CPC (source: EP US)

A47D 13/10 (2013.01 - EP US); **A63G 1/20** (2013.01 - EP); **A63G 19/12** (2013.01 - EP US)

Citation (search report)

- [XA] US 3203695 A 19650831 - PARKER FRED D
- [A] US 2651880 A 19530915 - KENNEDY EARL M
- [A] US 1627570 A 19270510 - MELCHER LEE W
- [A] US 1415831 A 19220509 - FREDERICKS HARRY A
- [AD] US 4045020 A 19770830 - TOWNSEND RAYMOND

Designated contracting state (EPC)

AT BE CH DK ES FI FR GB IT LI NL PT SE

DOCDB simple family (publication)

EP 0800848 A2 19971015; **EP 0800848 A3 19971112**; **EP 0800848 B1 20000531**; AT E193459 T1 20000615; DE 19609978 C1 19970522; DK 0800848 T3 20001009; ES 2148853 T3 20001016

DOCDB simple family (application)

EP 97102076 A 19970210; AT 97102076 T 19970210; DE 19609978 A 19960314; DK 97102076 T 19970210; ES 97102076 T 19970210