

Title (en)

Engine variable valve timing mechanism

Title (de)

Variable Ventilsteuerungsvorrichtung für Brennkraftmaschine

Title (fr)

Dispositif variable de commande des soupapes d'un moteur à combustion interne

Publication

EP 0801212 B1 20000726 (EN)

Application

EP 97105771 A 19970408

Priority

- JP 8648196 A 19960409
- JP 6412397 A 19970318

Abstract (en)

[origin: EP0801212A1] A variable valve timing mechanism is provided at the distal end of a camshaft (14; 25; 39; 55) for changing a valve timing of an engine valve (77). A rotor (11; 22; 52) is fixed to the distal end face of the camshaft (14; 25; 39; 55), and the rotor has four vanes (112; 222; 522) protruding radially outward. A housing (12; 24; 54) is disposed to surround the rotor (11; 22; 52) to be rotatable relative to the rotor (11; 22; 52) and the camshaft (14; 25; 39; 55), and the housing (12; 24; 54) has recesses (122; 242; 542) on the inner circumference. Each recess (122; 242; 542) is divided by the vane (112; 222; 522) into a first pressure chamber (101) and a second pressure chamber (102). A first passage (145; 255; 555) is defined in the camshaft (14; 25; 39; 55), for supplying a hydraulic fluid pressure to the first pressure chamber (101) so as to change the rotational phase of the second rotor (12; 13; 21; 23; 24; 51, 53, 54) with respect to the camshaft (14; 25; 39; 55), and the first passage (145; 255; 555) has an opening at the distal end face of the camshaft (14; 25; 39; 55). A second passage (148; 258; 558) is defined in the camshaft (14; 25; 39; 55), for supplying a fluid pressure to the second pressure chamber (102) so as to change the rotational phase of the second rotor (12; 13; 21; 23; 24; 51, 53, 54) with respect to the camshaft (14; 25; 39; 55), and the second passage (148; 258; 558) has an opening at outer circumference (149; 231) of the camshaft (14; 25; 39; 55). <IMAGE>

IPC 1-7

F01L 1/344; F16D 3/10

IPC 8 full level

F01L 3/14 (2006.01); **B21D 22/21** (2006.01); **B21K 1/22** (2006.01); **B23P 15/00** (2006.01); **F01L 1/34** (2006.01); **F01L 1/344** (2006.01); **F01L 3/02** (2006.01); **F01L 3/20** (2006.01); **F02D 13/02** (2006.01); **F16D 3/10** (2006.01)

CPC (source: EP KR US)

B21D 22/21 (2013.01 - EP US); **B21K 1/22** (2013.01 - EP US); **B23P 15/002** (2013.01 - EP US); **F01L 1/34** (2013.01 - KR); **F01L 1/3442** (2013.01 - EP US); **F01L 3/02** (2013.01 - EP US); **F01L 3/14** (2013.01 - EP US); **F01L 3/20** (2013.01 - EP US); **F16D 3/10** (2013.01 - EP US); **F01L 2001/34426** (2013.01 - EP US)

Cited by

EP1286023A3; DE10045418B4; DE19938596A1; DE19916675A1; DE19916675B4; DE19951391A1; DE19903594A1; DE19903594C2; WO0061920A1; US6763791B2; US8434438B2; WO2010003745A1; US6601554B1; US8490589B2; US6418893B1; US6170448B1; US6173687B1; US7707981B2; WO2006125536A1; WO0111202A1; WO2011061100A1

Designated contracting state (EPC)

DE FR GB

DOCDB simple family (publication)

EP 0801212 A1 19971015; EP 0801212 B1 20000726; CN 1090277 C 20020904; CN 1175658 A 19980311; DE 69702633 D1 20000831; DE 69702633 T2 20010405; ID 18168 A 19980312; JP 3077621 B2 20000814; JP H09329005 A 19971222; KR 100265982 B1 20001002; KR 19980076196 A 19981116; US 5724929 A 19980310

DOCDB simple family (application)

EP 97105771 A 19970408; CN 97111244 A 19970409; DE 69702633 T 19970408; ID 971164 A 19970407; JP 6412397 A 19970318; KR 19970012776 A 19970408; US 83525297 A 19970407