

Title (en)

PROCESS FOR SETTING ROOF BOLTS AND ADAPTER USED FOR CARRYING OUT THIS PROCESS

Title (de)

VERFAHREN ZUM SETZEN EINES GEBIRGSANKERS UND ADAPTERTEIL ZUR VERWENDUNG IN EINEM SOLCHEN VERFAHREN

Title (fr)

PROCEDE DE POSE D'UN BOULON D'ANCRAGE ET ADAPTATEUR UTILISE POUR METTRE EN OEUVRE CE PROCEDE

Publication

EP 0803014 A1 19971029 (DE)

Application

EP 95932715 A 19950912

Priority

- DE 4432472 A 19940913
- EP 9503574 W 19950912

Abstract (en)

[origin: DE4432472A1] A process for setting a roof bolt by using a self-drilling anchor is characterised in that the drilling anchor bar is coupled by an adapter to a drilling mechanism. A rinsing medium, for example water or air, or a setting medium, for example a mortar suspension, may be selectively guided through the adapter. The coupling between adapter, drilling mechanism and drilling anchor bar is maintained from the beginning of the drilling phase until the drilling hole is completely filled with setting medium. If required, the mixture of rinsing medium and mortar suspension that flows through the central cavity (5) and coupling section (3) of base body (1) into the drilling anchor bar may be continuously adjusted by means of the pipe connection (11) of the adapter, which is fixed in relation to the base body (1'). The adapter allows the roof bolt setting process to be significantly simplified, since it dispenses with numerous mounting and dismounting processes that are otherwise required in the area of the drilling mechanism at the end of the drilling phase.

IPC 1-7

E02D 5/76; E21D 20/02

IPC 8 full level

E02D 5/76 (2006.01); **E21D 20/02** (2006.01)

CPC (source: EP)

E02D 5/76 (2013.01); **E21B 21/02** (2013.01); **E21D 20/028** (2013.01)

Citation (search report)

See references of WO 9608606A1

Designated contracting state (EPC)

AT CH DE FR GB LI

DOCDB simple family (publication)

DE 4432472 A1 19960314; DE 4432472 C2 19970918; AU 3565895 A 19960329; EP 0803014 A1 19971029; TW 288077 B 19961011;
WO 9608606 A1 19960321

DOCDB simple family (application)

DE 4432472 A 19940913; AU 3565895 A 19950912; EP 9503574 W 19950912; EP 95932715 A 19950912; TW 84110700 A 19951012