

Title (en)

Primary cooling method in continuously annealing steel strips

Title (de)

Primärkühlverfahren für das kontinuierliche Glühen von Stahlbändern

Title (fr)

Procédé de refroidissement primaire pour le recuit en continu de bandes d'acier

Publication

EP 0803583 B1 20030723 (EN)

Application

EP 97105044 A 19970325

Priority

JP 13085196 A 19960426

Abstract (en)

[origin: EP0803583A2] In a primary cooling method in continuously annealing steel strips which comprises a heating step (A), a soaking step (B), a primary cooling step (C) including at least a rapid cooling step in a second half thereof, an overaging step (D), and a final cooling step (E), inert atmosphere gas containing H₂ gas is employed as cooling gas for use in the rapid cooling step and concentration of the H₂ gas is switched between two ranges of low and high concentrations of H₂ gas, depending on the required cooling rate of the rapid cooling step corresponding to the product grades of steel strips (26). Accordingly, the consumption of expensive H₂ gas is reduced thus enhancing the economy of the cooling operation while assuring the safety and efficiency of the primary cooling operation. <IMAGE>

IPC 1-7

C21D 9/573; **C21D 1/613**

IPC 8 full level

C21D 1/613 (2006.01); **C21D 9/573** (2006.01); **C21D 1/667** (2006.01)

CPC (source: EP)

C21D 1/613 (2013.01); **C21D 9/573** (2013.01); **C21D 1/667** (2013.01)

Cited by

EP1108793A1; EP1602738A1; US6533996B2; EP1228828A3; US6554926B2; US7381364B2; US7018584B2; US7763131B2; WO2015091138A3; US10400302B2

Designated contracting state (EPC)

AT DE GB

DOCDB simple family (publication)

EP 0803583 A2 19971029; **EP 0803583 A3 19990120**; **EP 0803583 B1 20030723**; **EP 0803583 B2 20091216**; AT E245710 T1 20030815; DE 69723608 D1 20030828; DE 69723608 T2 20040513; DE 69723608 T3 20100701

DOCDB simple family (application)

EP 97105044 A 19970325; AT 97105044 T 19970325; DE 69723608 T 19970325