

Title (en)
ENVELOPE WITH TEAR-OFF STRIP

Title (de)
BRIEFUMSCHLAG MIT AUFREISSLASCHE

Title (fr)
ENVELOPPE AVEC LANGUETTE D'OUVERTURE

Publication
EP 0807060 A1 19971119 (DE)

Application
EP 96946024 A 19961129

Priority
• DE 9602290 W 19961129
• DE 19544735 A 19951130

Abstract (en)
[origin: EP0990591A1] At least two weakened lines (1,2) are positioned on the mechanically produced right and left hand side of the letter envelope (5), packet or wrapper. When the envelope is produced, a tear-off strip (6) with double the thickness of paper and at least two weakened lines with one thickness of paper are produced. A second weakened line (3,4) preferably as a bend line is positioned above the first perforation line (1,2). The width of the strip matches the paper thickness. The tear-off strip is positioned preferably 10 millimetres from the inside of the envelope. A hole (8) is punched out of the bottom of the tear-off strip for gripping the inside, coloured, preferably green start (9) to the tear-off strip. The closure flap (12) on the side overlapped by the tear-off strip has a notch (11) or slot.

IPC 1-7
B65D 27/34

IPC 8 full level
B65D 27/34 (2006.01)

CPC (source: EP)
B65D 27/34 (2013.01)

Citation (search report)
See references of WO 9719863A1

Designated contracting state (EPC)
AT BE CH DE DK ES FI FR GB GR IE IT LI LU NL PT SE

DOCDB simple family (publication)
EP 0990591 A1 20000405; AT E192105 T1 20000515; AU 1867997 A 19970619; DE 19544735 A1 19970605; DE 19544735 C2 19970911; DE 59605054 D1 20000531; DK 0807060 T3 20000925; EP 0807060 A1 19971119; EP 0807060 B1 20000426; ES 2147949 T3 20001001; GR 3034018 T3 20001130; PT 807060 E 20001031; WO 9719863 A1 19970605

DOCDB simple family (application)
EP 99118531 A 19961129; AT 96946024 T 19961129; AU 1867997 A 19961129; DE 19544735 A 19951130; DE 59605054 T 19961129; DE 9602290 W 19961129; DK 96946024 T 19961129; EP 96946024 A 19961129; ES 96946024 T 19961129; GR 20000401704 T 20000726; PT 96946024 T 19961129