

Title (en)  
ENVELOPE WITH TEAR-OFF STRIP

Title (de)  
BRIEFUMSCHLAG MIT AUFREISSLASCHE

Title (fr)  
ENVELOPPE AVEC LANGUETTE D'OUVERTURE

Publication  
**EP 0807060 B1 20000426 (DE)**

Application  
**EP 96946024 A 19961129**

Priority  
• DE 9602290 W 19961129  
• DE 19544735 A 19951130

Abstract (en)  
[origin: EP0990591A1] At least two weakened lines (1,2) are positioned on the mechanically produced right and left hand side of the letter envelope (5), packet or wrapper. When the envelope is produced, a tear-off strip (6) with double the thickness of paper and at least two weakened lines with one thickness of paper are produced. A second weakened line (3,4) preferably as a bend line is positioned above the first perforation line (1,2). The width of the strip matches the paper thickness. The tear-off strip is positioned preferably 10 millimetres from the inside of the envelope. A hole (8) is punched out of the bottom of the tear-off strip for gripping the inside, coloured, preferably green start (9) to the tear-off strip. The closure flap (12) on the side overlapped by the tear-off strip has a notch (11) or slot.

IPC 1-7  
**B65D 27/34**

IPC 8 full level  
**B65D 27/34** (2006.01)

CPC (source: EP)  
**B65D 27/34** (2013.01)

Designated contracting state (EPC)  
AT BE CH DE DK ES FI FR GB GR IE IT LI LU NL PT SE

DOCDB simple family (publication)  
**EP 0990591 A1 20000405**; AT E192105 T1 20000515; AU 1867997 A 19970619; DE 19544735 A1 19970605; DE 19544735 C2 19970911; DE 59605054 D1 20000531; DK 0807060 T3 20000925; EP 0807060 A1 19971119; EP 0807060 B1 20000426; ES 2147949 T3 20001001; GR 3034018 T3 20001130; PT 807060 E 20001031; WO 9719863 A1 19970605

DOCDB simple family (application)  
**EP 99118531 A 19961129**; AT 96946024 T 19961129; AU 1867997 A 19961129; DE 19544735 A 19951130; DE 59605054 T 19961129; DE 9602290 W 19961129; DK 96946024 T 19961129; EP 96946024 A 19961129; ES 96946024 T 19961129; GR 20000401704 T 20000726; PT 96946024 T 19961129