

Title (en)
Printer

Title (de)
Drucker

Title (fr)
Imprimante

Publication
EP 0807523 A3 19980909 (EN)

Application
EP 97107925 A 19970515

Priority
• JP 12066496 A 19960515
• JP 12066596 A 19960515

Abstract (en)
[origin: EP0807523A2] A printer for printing on cut-sheet paper comprises a first insertion opening (27) for inserting cut-sheet paper (200), a combined discharge/insertion opening (18) for inserting and discharging cut-sheet paper (200), a paper feed path connecting said insertion opening (27) and said discharge/insertion opening (18), a printing area (4a, 8) provided in said paper feed path for printing on said cut-sheet paper (200), a first set of rollers (23, 24) disposed at the insertion opening side, a first open/close mechanism (37) for setting said first set of rollers (23, 24) into either an open state or a closed state, a second set of rollers (19, 20) disposed at the discharge opening side, and a second open/close mechanism (105, 106) for setting the said second set of rollers (19, 20) into either an open state or a closed state. In addition, means (37a, 107, 105a) are provided for coupling said first and second open/close mechanisms such that when one set of rollers is in its open state the other is in its closed state, and single drive means (104) for operating said first and second open/close mechanisms. <IMAGE>

IPC 1-7
B41J 11/48

IPC 8 full level
B41J 11/48 (2006.01); **B41J 13/28** (2006.01)

CPC (source: EP)
B41J 11/48 (2013.01); **B41J 13/28** (2013.01)

Citation (search report)
[A] US 5149217 A 19920922 - NARITA HIROSHI [JP]

Cited by
US8243905B2

Designated contracting state (EPC)
DE FR GB IT

DOCDB simple family (publication)
EP 0807523 A2 19971119; EP 0807523 A3 19980909; EP 0807523 B1 20011010; DE 69707194 D1 20011115; DE 69707194 T2 20020606

DOCDB simple family (application)
EP 97107925 A 19970515; DE 69707194 T 19970515