

Title (en)

Improved mounting device for lock cylinder of key-operated locks

Title (de)

Verbesserte Einbauvorrichtung für Schliesszylinder von mittels eines Schlüssels betätigten Schlössern

Title (fr)

Dispositif de fixation amélioré pour serrure de barillet cylindrique des serrures opérées par clef

Publication

**EP 0810340 B1 20020821 (DE)**

Application

**EP 97108628 A 19970528**

Priority

ES 9601472 U 19960529

Abstract (en)

[origin: EP0810340A2] The U-shaped trough body has vertical parallel walls with seat inside whose depth and breadth match with an oversize the cross-section of the radial attachment (1b) of the lock cylinder (1). The length of the trough equals the distance between the front of the door and back of a door plate (7) fixed on it and a point just in front of the back end of the lock cylinder. Cross-co-planar vanes are aligned with the front end of the trough and protrude at this end in opposite directions from the vertical walls of the trough. The vanes have openings for fixing the holder on the front of the door. The walls of the trough have bores (6) aligned crosswise with each other and with a threaded bore (1c) in the radial attachment of the lock cylinders.

IPC 1-7

**E05B 9/08**

IPC 8 full level

**E05B 9/08** (2006.01); **E05B 15/02** (2006.01)

CPC (source: EP)

**E05B 9/084** (2013.01); **E05B 15/02** (2013.01)

Cited by

EP1052350A1; CN109015486A

Designated contracting state (EPC)

AT BE DE FR GB IT NL

DOCDB simple family (publication)

**EP 0810340 A2 19971203**; **EP 0810340 A3 19980909**; **EP 0810340 B1 20020821**; AT E222635 T1 20020915; DE 59707994 D1 20020926; ES 1034271 U 19961216; ES 1034271 Y 19970501

DOCDB simple family (application)

**EP 97108628 A 19970528**; AT 97108628 T 19970528; DE 59707994 T 19970528; ES 9601472 U 19960529