

Title (en)
CIRCUIT FOR DRIVING A CONTACTOR

Title (de)
SCHALTUNGSAORDNUNG ZUR ANSTEUERUNG EINES SCHÜTZES

Title (fr)
CIRCUIT DE PILOTAGE POUR UN CONTACTEUR-DISJONCTEUR

Publication
EP 0811233 A1 19971210 (DE)

Application
EP 96902228 A 19960212

Priority

- DE 9600221 W 19960212
- DE 29503146 U 19950224

Abstract (en)
[origin: WO9626528A1] The new circuit has a control circuit (34), in which a switching element (2) and a measurement resistance (3) are connected in series to the contactor coil (1). A pick-up current regulating circuit (24) taps the voltage at the measurement resistance (3) and controls the switching element (2) after comparing said voltage to a reference voltage. By connecting in parallel another shunt resistance (41) to the measurement resistance (2), a current that is approximately twenty times higher in the pick-up phase than in the holding phase may be achieved with a single predetermined reference voltage. The parallel connection is cut off during the holding phase, so that only the measurement resistance (2) remains in activity.

IPC 1-7
H01H 47/10

IPC 8 full level
H01H 47/10 (2006.01); **H01H 47/32** (2006.01)

CPC (source: EP US)
H01H 47/10 (2013.01 - EP US); **H01H 47/32** (2013.01 - EP US)

Citation (search report)
See references of WO 9626528A1

Designated contracting state (EPC)
DE FR IT

DOCDB simple family (publication)
DE 29503146 U1 19950413; CN 1053061 C 20000531; CN 1169206 A 19971231; DE 59600435 D1 19980917; EP 0811233 A1 19971210;
EP 0811233 B1 19980812; US 5999396 A 19991207; WO 9626528 A1 19960829

DOCDB simple family (application)
DE 29503146 U 19950224; CN 96191539 A 19960212; DE 59600435 T 19960212; DE 9600221 W 19960212; EP 96902228 A 19960212;
US 89457697 A 19971013