

Title (en)  
CIRCUIT FOR DRIVING A CONTACTOR

Title (de)  
SCHALTUNGSANORDNUNG ZUR ANSTEUERUNG EINES SCHÜTZES

Title (fr)  
CIRCUIT DE PILOTAGE POUR UN CONTACTEUR-DISJONCTEUR

Publication  
**EP 0811233 B1 19980812 (DE)**

Application  
**EP 96902228 A 19960212**

Priority  
• DE 9600221 W 19960212  
• DE 29503146 U 19950224

Abstract (en)  
[origin: WO9626528A1] The new circuit has a control circuit (34), in which a switching element (2) and a measurement resistance (3) are connected in series to the contactor coil (1). A pick-up current regulating circuit (24) taps the voltage at the measurement resistance (3) and controls the switching element (2) after comparing said voltage to a reference voltage. By connecting in parallel another shunt resistance (41) to the measurement resistance (2), a current that is approximately twenty times higher in the pick-up phase than in the holding phase may be achieved with a single predetermined reference voltage. The parallel connection is cut off during the holding phase, so that only the measurement resistance (2) remains in activity.

IPC 1-7  
**H01H 47/10**

IPC 8 full level  
**H01H 47/10** (2006.01); **H01H 47/32** (2006.01)

CPC (source: EP US)  
**H01H 47/10** (2013.01 - EP US); **H01H 47/32** (2013.01 - EP US)

Designated contracting state (EPC)  
DE FR IT

DOCDB simple family (publication)  
**DE 29503146 U1 19950413**; CN 1053061 C 20000531; CN 1169206 A 19971231; DE 59600435 D1 19980917; EP 0811233 A1 19971210; EP 0811233 B1 19980812; US 5999396 A 19991207; WO 9626528 A1 19960829

DOCDB simple family (application)  
**DE 29503146 U 19950224**; CN 96191539 A 19960212; DE 59600435 T 19960212; DE 9600221 W 19960212; EP 96902228 A 19960212; US 89457697 A 19971013