

Title (en)
Process and headbox for a papermaking machine

Title (de)
Verfahren und Stoffauflauf für eine Papiermaschine

Title (fr)
Procédé et caisse de tête pour une machine à papier

Publication
EP 0812951 A2 19971217 (DE)

Application
EP 97106692 A 19970423

Priority
DE 19621258 A 19960525

Abstract (en)
[origin: DE19621258C1] The stock inlet, for a papermaking machine, has a flow chamber which is at least generally of the same width as the fourdrinier, leading into an outlet jet (3) with an outlet gap (3.3). The flow units (3.41,3.51,3.61) are located within the outlet jet assembly (3). The surfaces of the flow units, in contact with the fibre suspension, can be varied to increase or decrease them while in operation. Preferably the flow units (3.41,3.51,3.61) are mounted in pockets (3.4,3.5,3.6) for extension wholly or partially from them in the flow direction. In operation, the width of the outlet gap (3.3) is unchanged or it can be adjusted. The flow units can be plates which extend at least over part of the fourdrinier width. The flow units (3.41,3.51,3.61) can be cylindrical round rods, fitting into matching round openings in the pockets (3.4,3.5,3.6), and they are flexible for the pockets to impose a deflection on them as they are extended, or they are rigid. The flow deflection units can be hollow, and connected to a source of under- or over-pressure. The surfaces of the flow units (3.41,3.51,3.61) have zones of differing roughnesses, in the flow direction. They can be extended from their pockets by 10-300 mm and pref. 50-200 mm.

Abstract (de)
Die Erfindung betrifft ein Verfahren und einen Stoffauflauf für eine Papiermaschine mit einer Strömungskammer, die wenigstens annähernd gleich der Arbeitsbreite des Papiermaschinensiebes ist, und der eine Auslaufdüse mit einem Auslaufspalt nachgeschaltet ist; mit Strömungselementen, die in der Strömungskammer angeordnet sind; die von der Suspension berührten Flächen der Strömungselemente sind während des Betriebes des Stoffauflaufes veränderbar; die stromabwärtigen Enden der Strömungselemente sind ohne Einfluß auf die Weite des Auslaufspaltes. <IMAGE>

IPC 1-7
D21F 1/02

IPC 8 full level
D21F 1/00 (2006.01); **D21F 1/02** (2006.01)

CPC (source: EP)
D21F 1/02 (2013.01); **D21F 1/026** (2013.01); **D21F 1/028** (2013.01)

Designated contracting state (EPC)
DE FI SE

DOCDB simple family (publication)
DE 19621258 C1 19971016; CA 2206023 A1 19971125; DE 59710938 D1 20031211; EP 0812951 A2 19971217; EP 0812951 A3 19980401; EP 0812951 B1 20031105

DOCDB simple family (application)
DE 19621258 A 19960525; CA 2206023 A 19970523; DE 59710938 T 19970423; EP 97106692 A 19970423