

Title (en)

PROCESS CONTROL, METHOD AND APPARATUS

Title (de)

PROZESSTEUERUNG, VERFAHREN UND EINRICHTUNG

Title (fr)

GESTION DE PROCESSUS, PROCEDE ET APPAREIL

Publication

EP 0820572 A1 19980128 (EN)

Application

EP 96902349 A 19960214

Priority

- GB 9600309 W 19960214
- GB 9506365 A 19950328

Abstract (en)

[origin: GB2299414A] In a system to control the supply of combustion air to a reheat furnace 10 having a plurality of heating zones 10a, 10b, 10c, each having a burner 12a, 12b, 12c the pressure supplied by the supply unit 14 is set in accordance with the highest system resistance amongst the burners. A valve 18a-18c associated with each of the other zones is then closed to an extent to give the flow required in those zones. In an initialisation step, a resistance algorithm for each of the consumption units is determined with the valve associated with that unit in its maximum or desired opening position. The system resistance for each consumption unit is periodically calculated using these algorithms and the measured fluid flow or fluid demand to each of the units 12a-12c.

IPC 1-7

F23N 5/18; **F23N 3/08**; **F24F 11/04**

IPC 8 full level

F23N 3/08 (2006.01); **F23N 5/18** (2006.01); **F24F 11/04** (2006.01)

CPC (source: EP US)

F23N 3/082 (2013.01 - EP); **F23N 5/184** (2013.01 - EP); **F24F 11/74** (2017.12 - EP US); **F23N 2221/04** (2020.01 - EP); **F23N 2225/04** (2020.01 - EP); **F23N 2233/08** (2020.01 - EP); **F23N 2235/06** (2020.01 - EP)

Citation (search report)

See references of WO 9630703A1

Designated contracting state (EPC)

AT BE CH DE DK ES FR GB GR IE IT LI LU MC NL PT SE

DOCDB simple family (publication)

GB 2299414 A 19961002; **GB 2299414 B 19990407**; **GB 9603000 D0 19960410**; AU 4669396 A 19961016; EP 0820572 A1 19980128; GB 9506365 D0 19950517; WO 9630703 A1 19961003

DOCDB simple family (application)

GB 9603000 A 19960214; AU 4669396 A 19960214; EP 96902349 A 19960214; GB 9506365 A 19950328; GB 9600309 W 19960214