

Title (en)
Cathode ray tube displays having saddle-type deflecting coils

Title (de)
Kathodenstrahlröhrenanzeige mit Ablenkeinheit vom Satteltyp

Title (fr)
Dispositif d'affichage à tube à rayons cathodiques avec bobines de deflexion du type à selle

Publication
EP 0823723 B1 20031112 (EN)

Application
EP 96112723 A 19960807

Priority
EP 96112723 A 19960807

Abstract (en)
[origin: EP0823723A1] A cathode ray tube display which can reduce the temperature rise of its deflection yoke, not by using either extra-fine wires or litz wires but by increasing the heat radiation of its saddle-type coils, is provided. A deflection yoke (8) arranged in the rear periphery of a cathode ray tube display main body (1) comprises a saddle-type horizontal coil (4), an insulating frame (5) located outside of the saddle-type horizontal coil (4), a saddle-type vertical coil (6) and a ferrite core (7) located outside the insulating frame (5). The surface of the saddle-type horizontal coil (4) is partially exposed from the screen-side end face (9) of the ferrite core (7) toward the screen, and the surface area of the exposed part is predetermined to be from 100 to 298cm². Similarly, the exposed surface area of the saddle-type vertical coil (6) is predetermined to be from 55 to 185cm². <IMAGE>

IPC 1-7
H01J 29/76

IPC 8 full level
H01J 29/00 (2006.01); **H01J 29/76** (2006.01)

CPC (source: EP)
H01J 29/006 (2013.01); **H01J 29/762** (2013.01)

Designated contracting state (EPC)
DE FR GB IT NL SE

DOCDB simple family (publication)
EP 0823723 A1 19980211; **EP 0823723 B1 20031112**; DE 69630685 D1 20031218; DE 69630685 T2 20040923

DOCDB simple family (application)
EP 96112723 A 19960807; DE 69630685 T 19960807