

Publication

**EP 0831196 A3 19980401**

Application

**EP 97116081 A 19970916**

Priority

DE 19639235 A 19960924

Abstract (en)

[origin: EP0831196A2] The lock has a bolt (4) pretensioned in its locking position and provided with a blocking element (11) which interacts with an attachment (12) in the lock body (1) so that with improper activity on the lock the bolt (4) cannot be moved into its unlocking position. The blocking element and/or attachment form a rear cut section and engage or hook with each other in the blocking position. The blocking element can be formed by a projection (11) or notch on the bolt.

IPC 1-7

**E05B 17/20**; **E05B 67/00**

IPC 8 full level

**E05B 17/20** (2006.01); **E05B 67/00** (2006.01); **E05B 67/06** (2006.01)

CPC (source: EP)

**E05B 17/2084** (2013.01); **E05B 67/00** (2013.01); **E05B 67/003** (2013.01); **E05B 67/063** (2013.01)

Citation (search report)

- [X] US 5531487 A 19960702 - BERESHEIM THOMAS H [US]
- [A] US 3039807 A 19620619 - AGNESE JOSEPH M
- [A] US 3414307 A 19681203 - RUSSELL FRED J

Cited by

US11585119B2; EP3741932A1

Designated contracting state (EPC)

AT BE CH DE DK ES FI FR GB GR IE IT LI LU MC NL PT SE

DOCDB simple family (publication)

**EP 0831196 A2 19980325**; **EP 0831196 A3 19980401**; **EP 0831196 B1 20030806**; DE 19639235 A1 19980326; DE 59710535 D1 20030911

DOCDB simple family (application)

**EP 97116081 A 19970916**; DE 19639235 A 19960924; DE 59710535 T 19970916