

Title (en)  
Cooling panel for shaft furnace

Title (de)  
Wandkühlelement für Schachttöfen

Title (fr)  
Panneau de refroidissement pour four à cuve

Publication  
**EP 0837144 A1 19980422 (DE)**

Application  
**EP 97115379 A 19970905**

Priority  
DE 29616509 U 19960923

Abstract (en)  
The cooling element (1) for the wall of a shaft furnace is a hollow body forming at least one chamber (2,3). The hollow body of the cooling element (1) is fitted to the steel jacket of the furnace by suspension hooks. The cooling element (1) forms two adjacent chambers (2,3), as a unit, with an inner and outer chamber (2,3), each with water feed and outlet (7,8). Flow bodies (9) in the chambers (2,3) equalise the water flow. The flow guides (9) are guide plates, to form water channels, alternating at the opposite sides of the element (1). The water inlet (7) is at the start of the water channels and the outlet (8) is at their end. The flow guides (9) can have a teardrop shape, or they can be at an angle between the base and cover of a chamber (2,3). The cooling element (1) has upper and lower hooks to engage matching hooks at the furnace steel jacket. The connections for the water feeds and outlet (7,8) toward the steel jacket at the element (1) are threaded for the water tubes through the jacket to be screwed home. The cooling element (1) is a casting of cast iron or copper, or is produced by welding steel or copper plates. The flow bodies (9) can be profiles, at least at the base zone of the cooling element (1). The cooling element (1) has profiles on the side towards the furnace.

Abstract (de)  
Wandkühlelemente für Schachttöfen, insbesondere für Hochöfen, beispielsweise aus Grauguß oder Kupfer, bestehen im wesentlichen aus ofenseitig am Hochofenpanzer (6) befestigbaren, und im Inneren einen kammerartigen Hohlraum aufweisenden, kastenartigen flachen Kühlelementen (1), wobei der Hohlraum am unteren Ende mit einem Kühlmittelzu- (7) und am oberen Ende mit einem Kühlmittelauslauf (8) versehen ist, und zwischen Zulauf und Auslauf eine Kühlmittelführung vorgesehen ist. Zur herstellungstechnischen und wirtschaftlichen Vereinfachung sind in dem Hohlraum eines Kühlelementes (1) zwischen Boden (19) und Decke (20) das Kühlmittel in der Breite und Höhe gleichmäßig verteilende Strömungskörper (9; 21) angeordnet und das kastenartige Kühlelement (1) ist über mindestens am oberen und unteren Ende bodenseitig vorgesehene Hakenelemente (4) und mit diesen am Ofenpanzer (6) korrespondierende Hakenelemente (5) befestigbar ausgebildet. <IMAGE>

IPC 1-7  
**C21B 7/10; F27D 1/12**

IPC 8 full level  
**C21B 7/10** (2006.01); **F27B 1/24** (2006.01); **F27D 1/12** (2006.01); **F28F 27/02** (2006.01); **F27D 9/00** (2006.01)

CPC (source: EP)  
**C21B 7/10** (2013.01); **F27B 1/24** (2013.01); **F27D 1/12** (2013.01); **F28F 9/0265** (2013.01); **F28F 13/06** (2013.01); **F27D 2009/004** (2013.01); **F28D 2021/0078** (2013.01)

Citation (search report)  
• [YA] FR 2323113 A1 19770401 - SOFRESID [FR]  
• [A] DE 3335976 A1 19850221 - STEINFURTER EISENWERK GMBH [DE]  
• [A] FR 2459436 A1 19810109 - PROVENCE CONST MET  
• [A] DE 3313998 A1 19831208 - VOEST ALPINE AG [AT]  
• [A] US 1371906 A 19210315 - KNOX LUTHER L  
• [A] GB 2176883 A 19870107 - HYLSA SA  
• [A] DE 2653042 A1 19780524 - ROHDE EWALD W DR ING  
• [A] US 4787605 A 19881129 - KAPTEIN FRANK [NL]  
• [A] FR 2533306 A1 19840323 - INST OCHISTKE T [SU]  
• [A] EP 0705906 A1 19960410 - GUTEHOFFNUNGSHUETTE MAN [DE]  
• [A] DE 1758587 A1 19710311 - ROHDE EWALD W DR ING  
• [Y] PATENT ABSTRACTS OF JAPAN vol. 095, no. 007 31 August 1995 (1995-08-31)  
• [A] PATENT ABSTRACTS OF JAPAN vol. 005, no. 049 (C - 049) 8 April 1981 (1981-04-08)

Cited by  
LU90644B1; US7070733B2; WO2004097054A1; US6843958B1; WO0120045A1

Designated contracting state (EPC)  
BE DE FR GB NL SE

DOCDB simple family (publication)  
**DE 29715971 U1 19971113**; DE 29616509 U1 19961114; EP 0837144 A1 19980422

DOCDB simple family (application)  
**DE 29715971 U 19970905**; DE 29616509 U 19960923; EP 97115379 A 19970905