

Publication

EP 0838616 A3 19980513

Application

EP 97890197 A 19971003

Priority

AT 187996 A 19961028

Abstract (en)

[origin: EP0838616A2] For a contact-free scanning of the position of the piston a ring magnet (17) is provided on the piston (2). On at least one side of the ring magnet in addition to this and the sealing rings (15,16), the piston has a guide ring (18,19) of resistant material adjoining the inner wall of the cylinder to guide and centre same. The sealing rings can be provided on both ends and guide rings can be fitted on both sides of the ring magnet which is mounted between the sealing rings. At least one guide ring can be formed as an integral collar of the piston. The guide rings have a larger outer diameter than the ring magnet but smaller outer diameter than the sealing rings.

IPC 1-7

F16J 15/32; **F15B 15/28**

IPC 8 full level

F16J 1/04 (2006.01); **F15B 15/28** (2006.01); **F16J 9/00** (2006.01)

CPC (source: EP)

F15B 15/2807 (2013.01); **F15B 15/2861** (2013.01)

Citation (search report)

- [X] DE 2917232 A1 19791108 - HYDRO PNEUMATIC AB
- [A] EP 0301845 A1 19890201 - NORGREN MARTONAIR LTD [GB]
- [A] EP 0093859 A2 19831116 - BOSCH GMBH ROBERT [DE]
- [A] DE 2614263 A1 19771013 - HUNGER WALTER
- [A] CH 483569 A 19691231 - HOERBIGER VENTILWERKE AG [AT]
- [A] DE 4122481 A1 19930107 - KUHNKE GMBH KG H [DE]
- [A] DE 3015258 A1 19811029 - FESTO MASCHF STOLL G [DE]

Designated contracting state (EPC)

AT BE CH DE DK ES FI FR GB GR IE IT LI LU MC NL PT SE

DOCDB simple family (publication)

EP 0838616 A2 19980429; **EP 0838616 A3 19980513**; AT 404290 B 19981027; AT A187996 A 19980215; CZ 343497 A3 19980513

DOCDB simple family (application)

EP 97890197 A 19971003; AT 187996 A 19961028; CZ 343497 A 19971029