

Title (en)
Method for controlling restart of weaving operation of loom

Title (de)
Verfahren zur Steuerung des Wiederanlaufs einer Webmaschine

Title (fr)
Procédé pour contrôler le redémarrage d'un métier à tisser

Publication
EP 0839939 A1 19980506 (EN)

Application
EP 97118839 A 19971029

Priority
JP 28681996 A 19961029

Abstract (en)
When weaving operation is stopped due to a weft insertion failure, the loom is driven in a backward direction so that pick finding is conducted and a defective weft yarn is removed. After that, the loom is reset to a start state. In this case, a shed is formed in accordance with a correction pattern SK_j (j=1, 2,...) instead of a regular shedding pattern SK_i. By setting the shedding size of the correction pattern SK_j to <MATH> the warp yarn is not in excessively large tension. In this manner, weft yarns woven into a fabric before the occurrence of weft insertion failure are not undesirably moved, thereby keeping the density of weft yarn uniform, and preventing filling bar in the fabric. <IMAGE>

IPC 1-7
D03D 51/00

IPC 8 full level
D03D 51/00 (2006.01)

CPC (source: EP)
D03D 51/002 (2013.01)

Citation (search report)

- [A] CH 668997 A5 19890215 - ZELLWEGER USTER AG
- [A] EP 0629725 A1 19941221 - RUETI AG MASCHF [CH]
- [A] DE 3642913 A1 19880804 - KAISER GMBH & CO KG [DE]
- [A] EP 0080581 A2 19830608 - NISSAN MOTOR [JP]
- [A] FR 2583435 A1 19861219 - PICANOL NV [FR]

Cited by
CN104153108A; EP1862573A1; US6953063B2; WO0234982A3; WO2016015674A1

Designated contracting state (EPC)
BE DE IT

DOCDB simple family (publication)
EP 0839939 A1 19980506; EP 0839939 B1 20020220; DE 69710552 D1 20020328; DE 69710552 T2 20021010; JP 3361241 B2 20030107;
JP H10130998 A 19980519

DOCDB simple family (application)
EP 97118839 A 19971029; DE 69710552 T 19971029; JP 28681996 A 19961029