

Title (en)  
Monodirectional esplagnolette

Title (de)  
Monodirektionaler Treibstangenverschluss

Title (fr)  
Crémone monodirectionnelle

Publication  
**EP 0841449 B1 20020123 (FR)**

Application  
**EP 97402560 A 19971028**

Priority  
FR 9613598 A 19961107

Abstract (en)  
[origin: EP0841449A1] The long bolt mechanism consists of a housing (1) fitted into a recess in the door or window frame and containing a rotary toothed plate (14) which can be turned through 90 degrees by a handle and a bar (15) with two studs (8) connected to the bolts and a rack (16) meshing with the teeth (17) of the plate (14). The greatest diameter of the toothed plate (14) is more or less equivalent to the width of the mechanism's housing, which has an aperture (18) in one side wall to receive the edge of the plate. The mechanism also has a spring-loaded vane (21) which lies parallel to the direction of the rack's travel and is aligned between the plate's centre of rotation and the points where it meshes with the rack.

IPC 1-7  
**E05C 9/02**

IPC 8 full level  
**E05C 9/02** (2006.01); **E05C 9/12** (2006.01); **E05B 15/00** (2006.01)

CPC (source: EP)  
**E05C 9/021** (2013.01); **E05B 15/0053** (2013.01)

Cited by  
IT201900013482A1; EP1452676A1; EP1650380A1; CN100422499C

Designated contracting state (EPC)  
AT BE CH DE DK ES FI GB GR IT LI NL PT SE

DOCDB simple family (publication)  
**EP 0841449 A1 19980513; EP 0841449 B1 20020123**; AT E212410 T1 20020215; CN 1198501 A 19981111; DE 69710027 D1 20020314;  
DE 69710027 T2 20020801; DK 0841449 T3 20020325; ES 2170929 T3 20020816; FR 2755461 A1 19980507; FR 2755461 B1 19981218;  
JP H10292707 A 19981104; PT 841449 E 20020731; TW 342422 B 19981011

DOCDB simple family (application)  
**EP 97402560 A 19971028**; AT 97402560 T 19971028; CN 97125979 A 19971106; DE 69710027 T 19971028; DK 97402560 T 19971028;  
ES 97402560 T 19971028; FR 9613598 A 19961107; JP 31919597 A 19971106; PT 97402560 T 19971028; TW 86116539 A 19971106