

Title (en)

HORIZONTAL WELDING METHOD AND WELDING EQUIPMENT

Title (de)

VERFAHREN ZUM HORIZONTALSCHWEISSEN UND SCHWEISSVORRICHTUNG

Title (fr)

PROCEDE DE SOUDAGE HORIZONTAL ET APPAREILLAGE DE SOUDAGE

Publication

EP 0844039 A1 19980527 (EN)

Application

EP 97920937 A 19970507

Priority

- JP 9701533 W 19970507
- JP 14063896 A 19960510

Abstract (en)

In order to enable highly efficient welding without the generation of weld defect such as undercut, overlap, and defective meeting angle, a plurality of additive wires (5a, 5b) are inserted into a melting pool (12) during horizontal welding, a unidirectional current is made to flow between the wires, and a magnetic field (9) is used to provide a magnetic field to the melting pool substantially in a direction perpendicular to a surface of a parent metal so as to cause the melting pool (12) to generate upward (antigravitational direction) Lorentz's force (11), whereby a molten metal is lifted upward to prevent dripping of the molten metal and to improve its bead shape. <IMAGE>

IPC 1-7

B23K 9/02; B23K 9/08; B23K 9/167; B23K 15/00; B23K 26/00

IPC 8 full level

B23K 9/08 (2006.01); **B23K 9/167** (2006.01); **B23K 9/173** (2006.01); **B23K 26/21** (2014.01); **B23K 26/24** (2006.01); **B23K 37/06** (2006.01)

CPC (source: EP US)

B23K 9/08 (2013.01 - EP US); **B23K 9/167** (2013.01 - EP US); **B23K 9/1675** (2013.01 - EP US); **B23K 9/1735** (2013.01 - EP US);
B23K 15/0046 (2013.01 - EP US); **B23K 26/1423** (2013.01 - EP US); **B23K 26/24** (2013.01 - EP US); **B23K 26/348** (2015.10 - EP US);
B23K 37/06 (2013.01 - EP US)

Cited by

CN109967879A; CN111168194A; CN103042306A; CN109365965A; CN102152011A

Designated contracting state (EPC)

DE FR GB

DOCDB simple family (publication)

WO 9743073 A1 19971120; DE 69717774 D1 20030123; DE 69717774 T2 20030918; EP 0844039 A1 19980527; EP 0844039 A4 19990721;
EP 0844039 B1 20021211; JP 3219413 B2 20011015; US 6023043 A 20000208

DOCDB simple family (application)

JP 9701533 W 19970507; DE 69717774 T 19970507; EP 97920937 A 19970507; JP 54071797 A 19970507; US 98335798 A 19980112