

Title (en)
Snap fit connection

Title (de)
Rasthalterung

Title (fr)
Fixation par encliquetage

Publication
EP 0847222 B1 20070725 (DE)

Application
EP 97120437 A 19971121

Priority
DE 19650460 A 19961205

Abstract (en)
[origin: EP0847222A2] The latch holder has an elongated hollow body (10) with a casing wall (11) enclosing an optional cross-sectional shape, bearing arrangements (12) transverse to the length of the body and connected to the casing wall and at least one spring tongue (17) connected to the casing wall but at an angle with respect to it and with a clamping edge (18) facing the associated bearing arrangement. The spring tongue has a protrusion (20) with a free end surface (21) which points in the opposite direction relative to the bearing arrangement associated with the spring tongue. For each protrusion there is an opening (19) in the casing wall which the protrusion enters when the spring tongue is elastically deformed.

IPC 8 full level
F16B 21/07 (2006.01); **H04R 1/02** (2006.01)

CPC (source: EP)
H04R 1/025 (2013.01)

Cited by
CN114408229A

Designated contracting state (EPC)
DE FR GB IT

DOCDB simple family (publication)
EP 0847222 A2 19980610; EP 0847222 A3 20050323; EP 0847222 B1 20070725; DE 19650460 A1 19980610; DE 19650460 C2 20010523; DE 59712864 D1 20070906

DOCDB simple family (application)
EP 97120437 A 19971121; DE 19650460 A 19961205; DE 59712864 T 19971121