

Publication

EP 0849090 A3 19980701

Application

EP 96203632 A 19961219

Priority

EP 96203632 A 19961219

Abstract (en)

[origin: EP0849090A2] The present invention provides an imaging element for making a lithographic printing plate comprising on a flexible support (i) an ink repellent layer containing a crosslinked hydrophilic binder and (ii) a thermosensitive layer comprising hydrophobic thermoplastic polymer particles dispersed in a hydrophilic binder, characterized in that an outermost layer is present on top of said imaging element on the opposite side of the support, said outermost layer comprising at least a solid or liquid lubricant in a hydrophilic binder.

IPC 1-7

B41M 5/36; B41C 1/10

IPC 8 full level

B41C 1/10 (2006.01); B41M 5/36 (2006.01); B41N 1/14 (2006.01); G03F 7/00 (2006.01)

CPC (source: EP)

B41C 1/1025 (2013.01); B41M 5/366 (2013.01); B41C 2201/04 (2013.01); B41C 2201/14 (2013.01); B41C 2210/06 (2013.01); B41C 2210/08 (2013.01); B41C 2210/14 (2013.01); B41C 2210/20 (2013.01); B41C 2210/22 (2013.01); B41C 2210/24 (2013.01); B41C 2210/262 (2013.01)

Citation (search report)

- [A] FR 1561957 A 19690404
- [A] EP 0147624 A2 19850710 - IBM [US]
- [A] EP 0632328 A1 19950104 - AGFA GEVAERT NV [BE]
- [DA] J. VERMEESCH: "A LITHOGRAPHIC PRINTING PLATE", RESEARCH DISCLOSURE, no. 333, 1 January 1992 (1992-01-01), pages 2, XP000281114

Cited by

US7910286B2; US8679726B2; US6503684B1; EP1334841A3; EP1065049A1; EP1777067A1; CN111471508A; EP1685957A3; US6551757B1; EP3032334A1; WO2006133741A1; US7867572B2; EP2098376A1; EP2106924A1; WO2007045607A1; WO9851496A1; US7767384B2; WO2017157579A1; WO2017157572A1; WO2017157578A1; WO2017157571A1; WO2017157576A1; WO2017157575A1; US8419923B2; EP3637188A1; WO2020074258A1; EP2065211A1

Designated contracting state (EPC)

DE FR GB

DOCDB simple family (publication)

EP 0849090 A2 19980624; EP 0849090 A3 19980701; JP H10193824 A 19980728

DOCDB simple family (application)

EP 96203632 A 19961219; JP 36390797 A 19971218