

Title (en)
ELECTROMAGNETIC DEVICE FOR USE WITH A CONTINUOUS-CASTING MOULD

Title (de)
ELEKTROMAGNETISCHE EINRICHTUNG FÜR EINE STRANGGIESSKOKILLE

Title (fr)
DISPOSITIF ELECTROMAGNETIQUE POUR COQUILLE DE COULEE EN CONTINU

Publication
EP 0850116 B1 19990324 (DE)

Application
EP 96932449 A 19960813

Priority
• DE 9601554 W 19960813
• DE 19533577 A 19950829

Abstract (en)
[origin: US6021842A] PCT No. PCT/DE96/01554 Sec. 371 Date Jun. 1, 1998 Sec. 102(e) Date Jun. 1, 1998 PCT Filed Aug. 13, 1996 PCT Pub. No. WO97/07911 PCT Pub. Date Mar. 6, 1997A stationary continuous casting mold, especially for casting steel, with an electromagnetic device having a plurality of stirrer elements which are arranged in pairs on the outer wall of the continuous casting mold at a distance from one another and are connected to an electric a.c. voltage. The stirrer elements include at least two pairs and the stirrer elements of each pair are arranged opposite one another and so as to be rotated at an angle relative to one another in an X-shaped configuration in a plane parallel to the casting direction. All pairs are arranged at substantially the same height.

IPC 1-7
B22D 11/10

IPC 8 full level
B22D 11/04 (2006.01); **B22D 11/10** (2006.01); **B22D 11/115** (2006.01)

CPC (source: EP KR US)
B22D 11/10 (2013.01 - KR); **B22D 11/115** (2013.01 - EP US)

Designated contracting state (EPC)
AT DE FR GB IT

DOCDB simple family (publication)
US 6021842 A 20000208; AT E177975 T1 19990415; AU 7124796 A 19970319; CN 1072058 C 20011003; CN 1194601 A 19980930; DE 19533577 C1 19961024; DE 59601517 D1 19990429; EP 0850116 A1 19980701; EP 0850116 B1 19990324; JP 2942361 B2 19990830; JP H11500362 A 19990112; KR 100264946 B1 20000901; KR 19990028576 A 19990415; WO 9707911 A1 19970306

DOCDB simple family (application)
US 2956498 A 19980601; AT 96932449 T 19960813; AU 7124796 A 19960813; CN 96196594 A 19960813; DE 19533577 A 19950829; DE 59601517 T 19960813; DE 9601554 W 19960813; EP 96932449 A 19960813; JP 50969497 A 19960813; KR 19970709897 A 19971230