

Title (en)
Internal cooling blade of a turbo-machine

Title (de)
Innengekühlte Turbomaschinenschaufel

Title (fr)
Aube de turbomachine avec refroidissement interieur

Publication
EP 0851095 B1 20020925 (DE)

Application
EP 97810917 A 19971127

Priority
DE 19654115 A 19961223

Abstract (en)
[origin: EP0851095A1] A gas turbine blade (W) cooling device has an external flow of hot medium, and an internal coolant flow and involves thermal bridging. This is formed by pegs (S) of material melting at a high temperature, and having higher thermal conductivity than the wall. These project internally into the coolant flow. Preferably the pegs are made of synthetic diamond, made using the C-14 isotope. They are cast into the wall. The space cooled is the closed narrow gap (E) at the rear edge of an internally-cooled gas turbine. The gap and line of pegs, extend over the length of the blade.

IPC 1-7
F01D 5/18; F28F 3/02; F28F 1/10

IPC 8 full level
F01D 5/18 (2006.01); **F01D 9/02** (2006.01); **F28F 1/10** (2006.01); **F28F 1/12** (2006.01); **F28F 3/02** (2006.01)

CPC (source: EP)
F01D 5/187 (2013.01); **F28F 1/124** (2013.01); **F28F 3/022** (2013.01); **F05D 2260/221** (2013.01)

Designated contracting state (EPC)
DE FR GB IT

DOCDB simple family (publication)
DE 19654115 A1 19980625; CN 1186151 A 19980701; DE 59708321 D1 20021031; EP 0851095 A1 19980701; EP 0851095 B1 20020925; JP H10196304 A 19980728

DOCDB simple family (application)
DE 19654115 A 19961223; CN 97125588 A 19971222; DE 59708321 T 19971127; EP 97810917 A 19971127; JP 35364197 A 19971222