

Title (en)

Negative voltage charge pump, particularly for flash EEPROM memories.

Title (de)

Ladungspumpe mit negativer Ausgangsspannung, insbesondere für Flash-EEPROM-Speicher

Title (fr)

Pompe de charge à tension de sortie négative, en particulier pour mémoire EEPROM flash

Publication

EP 0851561 A2 19980701 (EN)

Application

EP 97830710 A 19971223

Priority

IT RM960899 A 19961223

Abstract (en)

A voltage multiplier circuit for integrated circuits, comprising two mirrored sections driven by control signals (PH00, PH01, PH0_N; PH10, PH11, PH1_N) generated by a logic circuitry which receives, as input signals, an enable signal (en) and a clock signal (clk), wherein each mirrored section includes N stages and each stage comprises a capacitor (C00, C01, C02; C10, C11, C12, C13) having a lower terminal and an upper terminal, the lower terminal is connected to a first switch (INV0, PCH01, PCH03, PCH05; INV1, PCH11, PCH13, PCH15) that, in closed condition, couples the lower terminal of the capacitor to the power supply voltage (Vpp), said lower terminal of the capacitor being additionally connected to a second switch (INV0, NCH00, NCH01, NCH02; INV1, NCH10, NCH11, NCH12) that, in closed condition, couples the lower terminal of the capacitor to ground voltage (GND), as far as the first stage is concerned, or to the upper terminal of the capacitor of the previous stage, the upper terminal of the capacitor is connected to a third switch (PCH00, PCH02, PCH04, PCH06; PCH10, PCH12, PCH14, PCH16) that, in closed condition, couples the upper terminal of the capacitor to ground (GND), the upper terminal of the capacitor (C03; C13) of the N-th stage is connected to a last switch (PCH014; PCH114) that, in closed in condition, couples the upper terminal of the capacitor of the N-th stage to the output of the voltage multiplier; said control signals directly or indirectly drive said switches such that, when the voltage multiplier is enabled (en = 1), at a rate determined by said clock signal (clk), each mirrored section in alternated times is switched over from a charging phase to a discharging phase, so that while a mirrored section is in charging phase, the other one is in discharging phase and vice versa; when a mirrored section of the circuit is charging phase, the last switch (PCH014; PCH114) and all second switches thereof (INV0, NCH00, NCH01, NCH02; INV1, NCH10, NCH11, NCH12) are in open condition, while its first (INV0, PCH01, PCH03, PCH05; INV1, PCH11, PCH13, PCH15) and its third switches (PCH00, PCH02, PCH04, PCH06; PCH10, PCH12, PCH14, PCH16) are in closed condition, so that all capacitors of this circuit section are parallel connected between the supply voltage (Vpp) and ground (GND) and are charged up to a voltage corresponding to said supply voltage (Vpp), with the upper plate at ground and the lower plate at the supply voltage (Vpp); when a mirrored section of the circuit is in discharging phase, all its first (INV0, PCH01, PCH03, PCH05; INV1, PCH11, PCH13, PCH15) and third switches (PCH00, PCH02, PCH04, PCH06; PCH10, PCH12, PCH14, PCH16) are in open condition, while its last switch (PCH014; PCH114) and all its second switches (INV0, NCH00, NCH01, NCH02; INV1, NCH10, NCH11, NCH12) are in closed condition, so that all capacitors are serially connected with one another, the lower terminal of the capacitor (C00; C10) of the first stage being connected to the ground voltage (GND) and the upper terminal of the capacitor of the N-th stage being connected to the output of the voltage multiplier; when the voltage multiplier is disabled (en = 0), both mirrored sections of the circuit are in charging phase. <IMAGE>

IPC 1-7

H02M 3/07

IPC 8 full level

G11C 5/14 (2006.01); **H02M 3/07** (2006.01)

CPC (source: EP US)

G11C 5/145 (2013.01 - EP US); **H02M 3/073** (2013.01 - EP US)

Cited by

US6967523B2; US11476849B2; US10886911B2; US10804892B2; US10505530B2; US10862473B2; US10790390B2; US10797172B2; US9608619B2; US9831857B2; US10236872B1; US10622990B2; US10622993B2; US10680600B2; US10790820B2; US10797694B2; US10797691B1; US10812068B2; US10818796B2; US11018662B2; USRE48944E; US11418183B2; US11870431B2

Designated contracting state (EPC)

DE FR GB IT NL

DOCDB simple family (publication)

EP 0851561 A2 19980701; **EP 0851561 A3 19990630**; **EP 0851561 B1 20020227**; DE 69710697 D1 20020404; DE 69710697 T2 20020905; IT 1290168 B1 19981019; IT RM960899 A0 19961223; IT RM960899 A1 19980623; US 5994949 A 19991130

DOCDB simple family (application)

EP 97830710 A 19971223; DE 69710697 T 19971223; IT RM960899 A 19961223; US 99447097 A 19971219