

Title (en)

THREAD FEED DEVICE FOR ELASTIC YARN

Title (de)

FÄDENLIEFERGERÄT FÜR ELASTISCHE GARNE

Title (fr)

DISTRIBUTEUR DE FIL ELASTIQUE

Publication

EP 0853696 A1 19980722 (DE)

Application

EP 96938936 A 19960917

Priority

- DE 9601749 W 19960917
- DE 19537215 A 19951006

Abstract (en)

[origin: DE19537215A1] The proposed thread feed device (1) is intended for elastic yarn (threads) on knitting machines in which the thread consumption fluctuates markedly with time and reaches high levels for certain periods. The device takes the form of a thread regulating wheel. The thread feed device (1) has a thread wheel (11) around which the thread to be delivered (2) is wound several times and which feeds the thread (2) into a thread store (19) situated between the knitting machine and the thread wheel (11). The thread store takes the form of a substantially straight section of the thread path. To monitor the thread tension, a tension sensor (22) is provided; its measurement path is vanishingly small compared to the length of thread to be stored in the thread store (19). The measurement path is defined by a mobile element (25) of the sensor device (22) and is aligned at right angles to the path of the thread. The connection of a low-inertia drive device (9) to a thread store (19) which exploits the characteristic elasticity of the thread and a regulator (24) which monitors the thread tension with the aid of a sensor device (22) permits the use of the thread feed device (1) for feeding elastic yarn and to keep the thread tension more or less constant even where the thread take-up fluctuates markedly with time. Since the thread (2) in the thread store (19) is not deflected and, in particular, is not subjected to a significant friction, and since the thread (2) reaches the thread wheel (11) without the aid of an intermediate thread brake, short returns of thread (2) can be caught by short reverse turns of the thread wheel (11).

IPC 1-7

D04B 15/50

IPC 8 full level

B65H 59/40 (2006.01); **D04B 15/50** (2006.01)

CPC (source: EP KR US)

B65H 59/40 (2013.01 - EP US); **D04B 15/50** (2013.01 - EP KR US); **B65H 2553/21** (2013.01 - EP US); **B65H 2553/26** (2013.01 - EP US); **B65H 2701/319** (2013.01 - EP US)

Citation (search report)

See references of WO 9713907A1

Designated contracting state (EPC)

DE ES FR GB GR IT

DOCDB simple family (publication)

DE 19537215 A1 19970410; DE 19537215 C2 19990902; AR 003796 A1 19980909; AU 7618696 A 19970430; BR 9610786 A 19990713; CA 2233647 A1 19970417; CA 2233647 C 20020319; CN 1072287 C 20011003; CN 1202940 A 19981223; CO 4600009 A1 19980508; CZ 102198 A3 19981014; CZ 287339 B6 20001011; DE 59606827 D1 20010531; EA 000316 B1 19990429; EA 199800269 A1 19981224; EP 0853696 A1 19980722; EP 0853696 B1 20010425; ES 2156301 T3 20010616; GR 3035884 T3 20010831; HK 1015835 A1 19991022; IL 123953 A 20010808; JP H11500499 A 19990112; KR 100302035 B1 20011029; KR 19990063971 A 19990726; TR 199800639 T1 19980622; TW 421682 B 20010211; UA 49851 C2 20021015; US 6079656 A 20000627; UY 24342 A1 19961101; WO 9713907 A1 19970417

DOCDB simple family (application)

DE 19537215 A 19951006; AR P960104604 A 19961004; AU 7618696 A 19960917; BR 9610786 A 19960917; CA 2233647 A 19960917; CN 96198510 A 19960917; CO 96052400 A 19961002; CZ 102198 A 19960917; DE 59606827 T 19960917; DE 9601749 W 19960917; EA 199800269 A 19960917; EP 96938936 A 19960917; ES 96938936 T 19960917; GR 20010400738 T 20010516; HK 99100933 A 19990308; IL 12395396 A 19960917; JP 51460897 A 19960917; KR 19980702446 A 19980403; TR 9800639 T 19960917; TW 85112136 A 19961004; UA 98041719 A 19960917; US 5115798 A 19980402; UY 24342 A 19961004