

Title (en)
DEVICE FOR CRIMPING OF SYNTHETIC BUNDLES OR SLIVERS OF YARNS

Title (de)
VORRICHTUNG ZUM KRÄUSELN VON SYNTHETISCHEN FADENBÜNDELN ODER -BÄNDERN

Title (fr)
DISPOSITIF DE FRISAGE DE FAISCEAUX OU DE RUBANS DE FILS SYNTHETIQUES

Publication
EP 0856071 A1 19980805 (DE)

Application
EP 96934674 A 19961014

Priority
• DE 19538423 A 19951016
• EP 9604461 W 19961014

Abstract (en)
[origin: US6009606A] PCT No. PCT/EP96/04461 Sec. 371 Date Mar. 5, 1998 Sec. 102(e) Date Mar. 5, 1998 PCT Filed Oct. 14, 1996 PCT Pub. No. WO97/14831 PCT Pub. Date Apr. 24, 1997A device for crimping synthetic bundles or slivers of yarns, the device has a stuffing box provided with an inlet for a yarn bundle or sliver and including a movable press plate and a stationary counter plate opposite to the press plate, two axially parallel rollers disposed at the inlet for the yarn bundle or sliver and forming a gap through which the yarn bundle or sliver enters the stuffing box, a pivot arm pivotally mounted on a stationary pivot bearing, one of the two axially parallel rollers being rotatably mounted at a fixed position in a machine frame, another of the two axially parallel rollers being seated on the pivot arm so as to be rotatable about a rotation axis thereof and the press plate being pivotally connected to the pivot arm by means of a rocker so as to be pivotable about the rotation axis of the roller seated on the pivot arm or another rotation axis parallel with the rotation axis of the roller seated on the pivot arm, whereby the gap between the rollers is varied, a contact pressure device for applying a contact-pressure force directed toward the counter plate to the press plate at an engagement point movable in a longitudinal direction of the stuffing box, an adjusting device for moving the engagement point of the contact-pressure forced on the press plate along the press plate, and a closed-loop control circuit unit for adjusting a reaction force acting between the rocker and the pivot arm to a predetermined fixed value by actuating the adjusting device.

IPC 1-7
D02G 1/12; G01N 33/36

IPC 8 full level
D02G 1/12 (2006.01); **G01N 33/36** (2006.01)

CPC (source: EP US)
D02G 1/12 (2013.01 - EP US); **D02G 1/125** (2013.01 - EP US)

Citation (search report)
See references of WO 9714831A1

Designated contracting state (EPC)
AT BE CH DE DK ES GB IT LI NL

DOCDB simple family (publication)
US 6009606 A 20000104; AT E182375 T1 19990815; DE 19538423 A1 19970417; DE 19538423 C2 19970821; DE 29617798 U1 19961212; DE 59602497 D1 19990826; EP 0856071 A1 19980805; EP 0856071 B1 19990721; ES 2136434 T3 19991116; JP 3059219 B2 20000704; JP H10512338 A 19981124; WO 9714831 A1 19970424

DOCDB simple family (application)
US 2945898 A 19980305; AT 96934674 T 19961014; DE 19538423 A 19951016; DE 29617798 U 19961014; DE 59602497 T 19961014; EP 9604461 W 19961014; EP 96934674 A 19961014; ES 96934674 T 19961014; JP 51550797 A 19961014