

Title (en)

SPRING ASSISTED MULTI-NOZZLE DESUPERHEATER

Title (de)

DAMPFKÜHLER MIT EINER UNTERSTÜTZUNGSFEDER UND MIT MEHREREN DÜSEN

Title (fr)

DESURCHAUFFEUR A PLUSIEURS INJECTEURS ASSISTE PAR UN RESSORT

Publication

EP 0856127 B1 20011212 (EN)

Application

EP 96930579 A 19960822

Priority

US 9613620 W 19960822

Abstract (en)

[origin: WO9808025A1] A steam desuperheater has a body (38) extending into a steam line (16) and is operated by a controlled variable water pressure source responding to the amount of superheat in the steam line. As the pressure of the supply line is increased above a predetermined level greater than the steam pressure in the steam line (16), a piston (50) moves up against a calibrated spring (61) to progressively uncover a plurality of spray openings (73, 76) so that increasing water pressure results in an increasingly greater amount of water sprayed into the steam line.

IPC 1-7

F22G 5/12

IPC 8 full level

F22G 5/12 (2006.01)

CPC (source: EP KR)

F22G 5/12 (2013.01 - KR); **F22G 5/123** (2013.01 - EP)

Designated contracting state (EPC)

DE ES FR GB SE

DOCDB simple family (publication)

WO 9808025 A1 19980226; CA 2233546 A1 19980226; CA 2233546 C 20021224; DE 69617984 D1 20020124; DE 69617984 T2 20020912; EP 0856127 A1 19980805; EP 0856127 B1 20011212; ES 2171225 T3 20020901; JP 3872818 B2 20070124; KR 100400691 B1 20031231; KR 20000064291 A 20001106

DOCDB simple family (application)

US 9613620 W 19960822; CA 2233546 A 19960822; DE 69617984 T 19960822; EP 96930579 A 19960822; ES 96930579 T 19960822; JP 51069498 A 19960822; KR 19980702897 A 19980421