

Title (en)

Blocking/releasing arrangement for a pivoting release element of an electrical striker

Title (de)

Sperr-/Freigabevorrichtung für eine Schwenkfalle eines Arbeitsstrom-Türöffners

Title (fr)

Dispositif de blocage et dégagement d'un élément pivotant d'une gâche électrique

Publication

EP 0861958 B1 20030604 (DE)

Application

EP 98102617 A 19980216

Priority

DE 19707759 A 19970226

Abstract (en)

[origin: EP0861958A2] The system for door opener has a locking lever (3), which locks or releases the catch (2). A first safety lever (6) holds the locking lever in the locked position, and with a solenoid (4) is swivelable in a position releasing the locking lever. With a second safety lever (10) which engages at the first safety lever (6), for the protecting of the locking lever against breaking open. The second safety lever is a mechanically uncouplable lever of small mass, located at its centre of gravity, which is adjustable from a position locking the first safety lever, by a magnetic coupling at an armature (5) of the solenoid, in a position releasing the first safety lever.

IPC 1-7

E05B 47/00; E05B 15/02

IPC 8 full level

E05B 15/02 (2006.01); **E05B 47/00** (2006.01); **E05B 47/04** (2006.01)

CPC (source: EP US)

E05B 47/0047 (2013.01 - EP US); **Y10T 292/1082** (2015.04 - EP US); **Y10T 292/688** (2015.04 - EP US); **Y10T 292/699** (2015.04 - EP US)

Cited by

ES2424824R1; EP3575518A1; EP2527570B1; EP2527570B2

Designated contracting state (EPC)

AT BE CH DE ES FR GB IT LI NL SE

DOCDB simple family (publication)

US 5988711 A 19991123; AT E242393 T1 20030615; CA 2229668 A1 19980826; CA 2229668 C 20020521; DE 19707759 C1 19980820;
DE 59808556 D1 20030710; EP 0861958 A2 19980902; EP 0861958 A3 20000628; EP 0861958 B1 20030604

DOCDB simple family (application)

US 2253498 A 19980212; AT 98102617 T 19980216; CA 2229668 A 19980216; DE 19707759 A 19970226; DE 59808556 T 19980216;
EP 98102617 A 19980216