

Title (en)  
Drive-cut off of a motor

Title (de)  
Antriebsabschaltung

Title (fr)  
Dispositif pour une déconnexion d'entraînement d'un moteur

Publication  
**EP 0864722 B1 20001227 (DE)**

Application  
**EP 98104573 A 19980313**

Priority  
DE 19710390 A 19970313

Abstract (en)  
[origin: EP0864722A2] The switch system for an electromotor, to switch the motor off according to the torque, has a torsion spring rod mounting between the stator and the fixed motor mounting. The switch (15,25) is within the housing, with a switch unit (17,27) at a relatively fixed intermediate section of the torsion rod or vice versa, to operate the switch (15,25) with the switching unit (17,27). The torsion spring rod is a quadrilateral rod (12), coaxial to the rotary axis of the armature (7) of the electromotor. One end (11) of the torsion rod is bonded to an armature plate (10), with its circumference secured to the housing, to transmit the force between the stator (8) and the end of the torsion rod.

IPC 1-7  
**E06B 9/88**

IPC 8 full level  
**E06B 9/88** (2006.01); **E06B 9/80** (2006.01)

CPC (source: EP)  
**E06B 9/88** (2013.01); **E06B 2009/6854** (2013.01)

Cited by  
EP2540946A3; ITMI20081518A1; FR2816465A1; US8666597B2; EP2886782A1; FR3014937A1; EP3163007A1; DE102015118492A1

Designated contracting state (EPC)  
DE FR IT

DOCDB simple family (publication)  
**EP 0864722 A2 19980916; EP 0864722 A3 19990414; EP 0864722 B1 20001227**; DE 19710390 A1 19980917; DE 59800398 D1 20010201

DOCDB simple family (application)  
**EP 98104573 A 19980313**; DE 19710390 A 19970313; DE 59800398 T 19980313