

Title (en)

Receiver for receiving digital audio programmes as well as the supplementary data contained in the audio programmes

Title (de)

Rundfunkempfänger für den Empfang von digitalen Tonprogrammen bzw. den digitalen Zusatzdaten, die in den Tonprogrammen enthalten sind

Title (fr)

Récepteur pour la réception de programmes audiophoniques numériques et des informations supplémentaires contenues dans le programme audiophonique

Publication

**EP 0865176 A2 19980916 (EN)**

Application

**EP 98102830 A 19980218**

Priority

- JP 5531897 A 19970310
- JP 6695197 A 19970319

Abstract (en)

The invention relates to a receiver of a transmission wave in which a specific information data signal and its validity identification data signal are transmitted by the same frequency band, in which the receiver desirably reproduces specific information only in a situation where the specific information can be truly reproduced in the reception system. A demodulating unit (31 to 36) receives the transmission wave and demodulates it to a predetermined digital signal. A decoding unit (38 and 40) decodes the digital signal, and a detecting unit 3B obtains an error amount of the digital signal recognized in the decoding process. An evaluating unit 3B evaluates the error amount, and a detecting unit 3A detects an identification data signal from a decoded output. The control part 3C (30) reproduces and outputs the specific information data signal concerning the identification data signal based on the evaluation result and the identification data signal. Even when a code rate of the specific information data signal to be information reproduced differs from that of the validity identification data signal, the specific data signal can be desirably information reproduced at a proper timing. The invention also relates to a digital audio signal receiver having a muting function for a reproduction audio sound and accomplishing a good muting operation even for a digital audio signal having no error detection code. A control part (30) obtains an error amount of a digital signal to be recognized in the decoding process and a muting block (42) effects the muting of an audio signal to be reproduced based on the digital signal at a muting level according to the error amount.

IPC 1-7

**H04H 1/00**

IPC 8 full level

**H04H 20/30** (2008.01); **H04H 20/55** (2008.01); **H04H 60/12** (2008.01)

CPC (source: EP)

**H04H 20/30** (2013.01); **H04H 20/55** (2013.01); **H04H 60/12** (2013.01); **H04H 2201/20** (2013.01)

Cited by

NL1030982C2; EP2461610A1; EP1885079A1; EP1037419A3; EP0961432A3; EP1104138A3; EP1850515A3; EP2323267A1; EP1404023A3; EP1727288A3; US7844279B2

Designated contracting state (EPC)

DE FR GB

DOCDB simple family (publication)

**EP 0865176 A2 19980916**; **EP 0865176 A3 20040901**

DOCDB simple family (application)

**EP 98102830 A 19980218**