

Title (en)

Device for fastening means for protection against sun or sight

Title (de)

Vorrichtung zum Befestigen von Sonnen- oder Blickschutzeinrichtungen

Title (fr)

Dispositif pour fixer des installations de protection solaire ou visuelle

Publication

EP 0866205 A1 19980923 (DE)

Application

EP 98104751 A 19980317

Priority

DE 19712117 A 19970322

Abstract (en)

The free ends (33a) of the clamp flanges (33, 35) are so sprung in relation to one another that before installation they are held at a distance which is smaller than the distance of the strip side surfaces (10), against which the clamp surfaces are to be pressed. The clamp flange free ends when the clamp shoe (31) is fitted onto the strip (11) are braced apart, with the formation of a closure force acting against the bracing effect. One of the clamp flanges (33, 35) works in conjunction with a fixture part (35a) for fitting the device. The fixture part on the one hand and the shoulder with the clamp flanges on the other hand comprise divided material pieces.

Abstract (de)

Die Erfindung bezieht sich auf eine Vorrichtung zum Befestigen von Sonnen- oder Blickschutzeinrichtungen an Holmen (8) von Fenstern, Türen odgl., die als Klemmschuh (31) auf eine Leiste (11) eines Holmes (8) aufklemmbar ist und die aus über eine Schulter (37) miteinander verbundenen Klemmflanschen (33,35) besteht, deren freie Enden (33a,35b) so gegeneinander federn, daß diese vor der Montage auf einem Abstand gehalten sind, der kleiner ist als der Abstand der Leistenseitenflächen (10), gegen die die Klemmflansche (33,35) zu drücken sind, wobei ein Befestigungsteil (35a) einerseits und die Schulter (37) mit den Klemmflanschen (33,35) andererseits aus getrennten Materialstücken bestehen und wobei der mit dem Befestigungsteil (35a) zum Anbringen der Einrichtungen zusammenwirkende Klemmflansch (35) derart in Richtung auf das an der Leiste (11) anliegende Befestigungsteil (35a) abgebogen und gegen das Befestigungsteil (35a) setzbar ist, daß der Klemmflansch (35) im montierten Zustand das Befestigungsteil (35a) gegen die Leiste (11) drückt. <IMAGE>

IPC 1-7

E06B 9/174; F16B 2/22

IPC 8 full level

E06B 9/174 (2006.01); **E06B 9/323** (2006.01); **E06B 9/42** (2006.01); **F16B 2/22** (2006.01)

CPC (source: EP)

E06B 9/323 (2013.01); **E06B 9/42** (2013.01)

Citation (search report)

- [X] GB 2233026 A 19910102 - PUTNINS ARVIDS
- [X] US 3994050 A 19761130 - BUB HANS WERNER ALFRED
- [DA] DE 8325110 U1 19831215
- [A] FR 2276493 A1 19760123 - LOEB SA [FR]
- [A] EP 0669470 A1 19950830 - RAPID SA [FR]

Cited by

BE1017937A4; EP1221530A3; EP1520955A3; DE202014104873U1; DE202018106139U1; EP1221530A2; DE202012103038U1; DE202012009191U1

Designated contracting state (EPC)

CH DE DK ES FR IT LI NL SE

DOCDB simple family (publication)

EP 0866205 A1 19980923; EP 0866205 B1 20010822; DE 19712117 A1 19981001; DE 59801236 D1 20010927; DK 0866205 T3 20011217

DOCDB simple family (application)

EP 98104751 A 19980317; DE 19712117 A 19970322; DE 59801236 T 19980317; DK 98104751 T 19980317