

Title (en)  
Discharge lamp of the short arc type

Title (de)  
Kurzbogenentladungslampe

Title (fr)  
Lampe à décharge à arc court

Publication  
**EP 0866492 A2 19980923 (EN)**

Application  
**EP 98104521 A 19980312**

Priority  
JP 8338697 A 19970318

Abstract (en)  
A discharge lamp of the short arc type with good light intensity stability in which arc fluctuation is suppressed is achieved, according to the invention by providing a discharge lamp of the short arc type which has an arc tube which surrounds the discharge space, hermetically sealed portions on the two ends of the arc tube, a cathode and an anode which are arranged opposite one another in the arc tube and which is operated such that the cathode is pointed upward, in by the cathode being supported by an inner lead which is held securely by the hermetically sealed portion, the outside diameter of the cathode being greater than the outside diameter of the inner lead, and by the relationship  $L \geq 2.5D$  being satisfied, where D is the outside diameter of the cathode (mm) and L is the axial length of the cathode (mm). <IMAGE>

IPC 1-7  
**H01J 61/86**; **H01J 61/073**

IPC 8 full level  
**G03F 7/20** (2006.01); **H01J 61/073** (2006.01); **H01J 61/86** (2006.01)

CPC (source: EP US)  
**G03F 7/70016** (2013.01 - EP US); **H01J 61/0732** (2013.01 - EP US); **H01J 61/86** (2013.01 - EP US)

Cited by  
WO03075310A1; EP0926701A1; US6163111A; WO03001563A1; US7279839B2

Designated contracting state (EPC)  
DE GB NL

DOCDB simple family (publication)  
**EP 0866492 A2 19980923**; **EP 0866492 A3 19990203**; **EP 0866492 B1 20030115**; DE 69810683 D1 20030220; DE 69810683 T2 20030918; JP 3298453 B2 20020702; JP H10261383 A 19980929; KR 100499618 B1 20051024; KR 19980080433 A 19981125; TW 385478 B 20000321; US 6107741 A 20000822

DOCDB simple family (application)  
**EP 98104521 A 19980312**; DE 69810683 T 19980312; JP 8338697 A 19970318; KR 19980009358 A 19980318; TW 87100252 A 19980109; US 4041198 A 19980318