

Title (en)  
Security cylinderlock having an increased picking resistance

Title (de)  
Zylindersicherheitsschloss mit erhöhtem Einbruchswiderstand

Title (fr)  
Cylindre de sûreté pour serrure ayant une protection améliorée contre l'effraction

Publication  
**EP 0874114 B1 20010523 (FR)**

Application  
**EP 98400179 A 19980129**

Priority  
FR 9705073 A 19970424

Abstract (en)  
[origin: EP0874114A1] The lock has a protective sleeve (1) containing a safety barrel with a stator (8) and rotor (9) controlled by a key. Between the forward end of the barrel and the sleeve the lock incorporates an anti-drilling plate (10) with a slot (11) for the key, and a guard ring (18) with a series of inserts (17). The inserts can be conical or curved in shape, having their pointed or curved faces towards the front of the lock and their axes parallel to that of the ring, which is fitted to a step (10) on the anti-drilling plate.

IPC 1-7  
**E05B 15/16**

IPC 8 full level  
**E05B 15/16** (2006.01)

CPC (source: EP)  
**E05B 15/1614** (2013.01); **E05B 2015/1628** (2013.01)

Cited by  
FR2882463A1; ITTV20130053A1; ITTV20120202A1; US7987688B2; FR2828226A1; WO2006089844A1; JP2008532217A

Designated contracting state (EPC)  
AT DE ES FR IT

DOCDB simple family (publication)  
**EP 0874114 A1 19981028; EP 0874114 B1 20010523**; AT E201476 T1 20010615; DE 69800819 D1 20010628; DE 69800819 T2 20011108;  
ES 2158650 T3 20010901; FR 2762637 A1 19981030; FR 2762637 B1 19990709

DOCDB simple family (application)  
**EP 98400179 A 19980129**; AT 98400179 T 19980129; DE 69800819 T 19980129; ES 98400179 T 19980129; FR 9705073 A 19970424