

Title (en)  
SELF-LUBRICATING SHEET COMPOSITE

Title (de)  
SELBSTSCHMIERENDER BLATTSATZ

Title (fr)  
MATÉRIAU COMPOSITE EN FEUILLE AUTO-LUBRIFIANT

Publication  
**EP 0874739 A1 19981104 (EN)**

Application  
**EP 96945013 A 19961219**

Priority  
• US 9620579 W 19961219  
• US 58606596 A 19960116

Abstract (en)  
[origin: WO9726142A1] A method for piercing or severing one or more sheets that have a layer of pressure sensitive adhesive along one surface. A layer of lubricating material that may be micro-encapsulated is positioned adjacent the layer of pressure sensitive adhesive. Severing or piercing the sheet will transfer a sufficient quantity of the lubricant to the implement doing the severing or piercing to restrict transfer of pressure sensitive adhesive to that implement.

IPC 1-7  
**B42D 5/00**; **B26D 7/08**

IPC 8 full level  
**B26D 7/08** (2006.01); **B42D 5/00** (2006.01)

CPC (source: EP)  
**B26D 7/088** (2013.01); **B42D 5/003** (2013.01)

Citation (search report)  
See references of WO 9726142A1

Designated contracting state (EPC)  
DE FR GB IT NL

DOCDB simple family (publication)  
**WO 9726142 A1 19970724**; AU 1347797 A 19970811; EP 0874739 A1 19981104

DOCDB simple family (application)  
**US 9620579 W 19961219**; AU 1347797 A 19961219; EP 96945013 A 19961219