

Title (en)

INDUSTRIAL DOOR HAVING ENHANCED SEALING PROPERTIES

Title (de)

INDUSTRIETOR MIT VERSTÄRKTER DICHTUNG

Title (fr)

PORTE DE MANUTENTION A ETANCHEITE RENFORCEE

Publication

**EP 0877850 A1 19981118 (FR)**

Application

**EP 97902400 A 19970130**

Priority

- FR 9700176 W 19970130
- FR 9601258 A 19960202

Abstract (en)

[origin: WO9728346A1] An industrial door comprising a movable screen (3) for sealing or opening an aperture, wherein said screen is advantageously vertically raisable and has two vertical edges (3D, 3G) defining the screen width (L) and being engageable with respective guides (1, 2). The bottom wall of each guide has a horizontal cross-section defining a first or moving area where the spacing (E) between the bottom walls of the guides is greater than the width (L) of the screen, and at least one second or sealing area where the spacing (E) between the bottom walls of the guides is smaller than the width (L) of the screen. When the screen is moved, its edges do not rub against the guides. When the screen is lowered, the wind pressure exerted on the screen urges the edges into engagement with the narrower portions of the guides.

IPC 1-7

**E06B 9/58**

IPC 8 full level

**E06B 9/02** (2006.01); **E06B 9/06** (2006.01); **E06B 9/13** (2006.01); **E06B 9/17** (2006.01); **E06B 9/58** (2006.01); **F25D 23/02** (2006.01)

CPC (source: EP)

**E06B 9/58** (2013.01); **F25D 23/021** (2013.01); **E06B 2009/586** (2013.01)

Citation (search report)

See references of WO 9728346A1

Designated contracting state (EPC)

BE CH DE ES FR GB IT LI LU NL PT SE

DOCDB simple family (publication)

**WO 9728346 A1 19970807**; CA 2244750 A1 19970807; EP 0877850 A1 19981118; FR 2744485 A1 19970808; FR 2744485 B1 19980410; JP 2000505849 A 20000516

DOCDB simple family (application)

**FR 9700176 W 19970130**; CA 2244750 A 19970130; EP 97902400 A 19970130; FR 9601258 A 19960202; JP 52736097 A 19970130