

Title (en)

DEVICE FOR APPLYING RELEASE AGENT TO THE SURFACE OF A FIXING ROLLER OF AN ELECTROGRAPHIC PRINTER OR COPIER

Title (de)

TRENNMITTELAUFTRAGSVORRICHTUNG ZUM AUFTRAGEN VON TRENNMITTEL AUF DIE OBERFLÄCHE EINER FIXIERWALZE EINES ELEKTROGRAFISCHEN DRUCK- ODER KOPIERGERÄTES

Title (fr)

DISPOSITIF POUR L'APPLICATION D'UN AGENT SEPARATEUR SUR LA SURFACE D'UN ROULEAU DE FIXAGE D'UNE MACHINE D'IMPRESSION OU DE COPIAGE ELECTROGRAPHIQUE

Publication

**EP 0877973 A1 19981118 (DE)**

Application

**EP 96934383 A 19960827**

Priority

- DE 9601588 W 19960827
- DE 19602774 A 19960126

Abstract (en)

[origin: WO9727518A1] Release agent (L) is conveyed by an applicator (V) to the surface of a fixing roller (F). The release agent (L) is fed to the applicator (V) through contact with a wick. The applicator (V) is a rolled web conveyed from a supply roller (VV) to a take-up roller (AV). The take-up roller (AV) is driven by a motor (MO) controlled by a control unit (CON). A sensor (H) detects the rotation speed of the supply roller (VV) and provides the control unit (CON) with corresponding information. The control unit (CON) assesses this information in such a way that the applicator (V) runs at a constant speed.

IPC 1-7

**G03G 15/20**

IPC 8 full level

**G03G 15/20** (2006.01)

CPC (source: EP US)

**G03G 15/2025** (2013.01 - EP US); **Y10S 118/01** (2013.01 - EP US)

Citation (search report)

See references of WO 9727518A1

Designated contracting state (EPC)

DE FR GB

DOCDB simple family (publication)

**WO 9727518 A1 19970731**; DE 59607330 D1 20010823; EP 0877973 A1 19981118; EP 0877973 B1 20010718; JP 2000503419 A 20000321; US 6070044 A 20000530

DOCDB simple family (application)

**DE 9601588 W 19960827**; DE 59607330 T 19960827; EP 96934383 A 19960827; JP 52639597 A 19960827; US 11731998 A 19981116