

Publication

EP 0878237 A3 19981230 (EN)

Application

EP 98110812 A 19950217

Priority

- DE 4404966 A 19940217
- DE 4419696 A 19940604
- EP 95912160 A 19950217

Abstract (en)

[origin: DE4404966A1] The base part (1) is made from an elastic material. A projection (3) set adjacent at least one spray hole (2) is connected to the base part. The outer surface of the projection (3) merges substantially continuously into the inner surface of the hole so that limescale on the base part of the spray head can be removed rapidly and easily. A support part (8) on the underneath of the spray head has openings (9). The base part rests directly or indirectly on the support part and at least one spray opening is provided in the area of the openings (9). On the outside of the base part there are studs which each project into the openings of the support part.

IPC 1-7

B05B 1/18; **B05B 15/02**

IPC 8 full level

B05B 1/18 (2006.01); **B05B 15/02** (2006.01); **B05B 15/528** (2018.01); **B05B 15/06** (2006.01)

CPC (source: EP US)

B05B 1/185 (2013.01 - EP US); **B05B 15/528** (2018.01 - EP); **B05B 15/62** (2018.01 - US)

Citation (search report)

- [A] DE 9303986 U1 19930812
- [A] US 5246301 A 19930921 - HIRASAWA NOBUO [JP]
- [A] US 2559894 A 19510710 - NORDELL CARL H

Cited by

WO2004085753A1

Designated contracting state (EPC)

DE FR IT

DOCDB simple family (publication)

DE 4404966 A1 19950831; **DE 4404966 C2 19970213**; DE 59509412 D1 20010816; DE 59509619 D1 20011025; EP 0878237 A2 19981118; EP 0878237 A3 19981230; EP 0878237 B1 20010711

DOCDB simple family (application)

DE 4404966 A 19940217; DE 59509412 T 19950217; DE 59509619 T 19950217; EP 98110812 A 19950217