

Title (en)

Glazing spacer block

Title (de)

Verglasungsklotz

Title (fr)

Bloc d'espacement pour vitrage

Publication

EP 0879932 A2 19981125 (DE)

Application

EP 98108402 A 19980508

Priority

DE 29709017 U 19970522

Abstract (en)

The glazing block has a longitudinal continuous centre groove (13) on the bearing surface side with the width (b) of the groove at most half the width (B) of one of the two webs (14) defining the groove. The groove is roughly half of the thickness of the block. The centre groove has between the groove base (15) and walls (16) base radii (17) corresponding to half the groove depth (t). The frame support face (12) formed by the webs is unprofiled.

Abstract (de)

Verglasungsklotz (10), der aus hochflexiblem Werkstoff besteht, insbesondere aus einem thermoplastischen Elastomer, mit einer Glasabstützfläche (11), und mit einer zu letzterer distanzierten Rahmenauflagefläche (12). Um einen Verglasungsklotz (10) mit den eingangs genannten Merkmalen so auszubilden, daß er nicht bruchgefährdet ist und trotzdem kein Belüftungshindernis ist, wird er so ausgebildet, daß der Klotz (10) eine auflageflächenseitig längs durchlaufende Mittelnut (13) aufweist, deren Breite höchstens halb so groß ist, wie die Breite eines der beiden die Mittelnut (13) begrenzenden Stege (14). <IMAGE>

IPC 1-7

E06B 3/54

IPC 8 full level

E06B 3/54 (2006.01)

CPC (source: EP)

E06B 3/5409 (2013.01)

Cited by

DE102016109913A1

Designated contracting state (EPC)

AT BE CH DE DK FR GB IT LI NL

DOCDB simple family (publication)

DE 29709017 U1 19980924; EP 0879932 A2 19981125; EP 0879932 A3 19991117

DOCDB simple family (application)

DE 29709017 U 19970522; EP 98108402 A 19980508