

Title (en)
MULTI-COAT PAINTING PROCESS

Title (de)
VERFAHREN ZUR MEHRSCHEIDLACKIERUNG

Title (fr)
PROCEDE POUR L'APPLICATION DE PEINTURE EN PLUSIEURS COUCHES

Publication
EP 0881954 B1 19990811 (DE)

Application
EP 97903326 A 19970219

Priority

- DE 19606716 A 19960223
- EP 9700784 W 19970219

Abstract (en)
[origin: DE19606716C1] A process for the multi-coat painting of a substrate with a first coat of a stoved dipping paint. Said process involves the application of a second coat with a dry thickness of 10 to 30 μm of a first aqueous base coating agent containing polyurethane resin and the wet-on-wet application of a third coat with a thinner dry thickness of 7 to 15 μm of a second aqueous base coating agent, the further application of a coat of clear lacquer without prior stoving, followed by stoving all together, where the first base coating agent has a higher polyurethane resin than the second.

IPC 1-7
B05D 7/00

IPC 8 full level
B05D 1/36 (2006.01); **B05D 7/00** (2006.01); **B05D 7/14** (2006.01)

CPC (source: EP US)
B05D 7/577 (2013.01 - EP US)

Cited by
CN103182371A

Designated contracting state (EPC)
BE DE ES FR GB IT NL PT SE

DOCDB simple family (publication)
DE 19606716 C1 19970814; AU 1792497 A 19970910; BR 9707608 A 19990727; DE 59700330 D1 19990916; EP 0881954 A1 19981209;
EP 0881954 B1 19990811; ES 2140962 T3 20000301; JP 2000505352 A 20000509; JP 4096069 B2 20080604; US 5976343 A 19991102;
WO 9730795 A1 19970828

DOCDB simple family (application)
DE 19606716 A 19960223; AU 1792497 A 19970219; BR 9707608 A 19970219; DE 59700330 T 19970219; EP 9700784 W 19970219;
EP 97903326 A 19970219; ES 97903326 T 19970219; JP 52978997 A 19970219; US 10127198 A 19981210