

Title (en)  
Lock and fitting system

Title (de)  
Schloss-Beschlag-System

Title (fr)  
Système de serrure et ferrure

Publication  
**EP 0882859 B1 20020410 (DE)**

Application  
**EP 98110326 A 19980605**

Priority  
DE 29709827 U 19970605

Abstract (en)  
[origin: EP0882859A1] The system comprises a mortise lock (10) with catch (12), bolt (14), a first profiled cylinder (18) adjacent to a cuff (16) (sic), and a second profiled cylinder (22) at the opposite side of the first to the cuff. The first cylinder is semi-cylindrical, giving a lock tongue movement of 180 degrees with a locking movement through 360 degrees. It can be actuated by a cylindrical or security key, while the second one can be actuated by a special inserted key. Both cylinders can be designed for operation from one side only, while the catch (12) can be actuated by one or more door-pawls. The second cylinder can be actuated by a hand lever from the opposite side.

IPC 1-7  
**E05B 35/10**; **E05B 41/00**; **E05B 65/10**

IPC 8 full level  
**E05B 35/10** (2006.01); **E05B 41/00** (2006.01); **E05B 63/00** (2006.01); **E05B 65/10** (2006.01)

CPC (source: EP)  
**E05B 35/10** (2013.01); **E05B 63/0069** (2013.01); **E05B 63/0017** (2013.01)

Cited by  
EP1936075A2; EP1936074A2; EP1936073A2; EP1936076A2

Designated contracting state (EPC)  
AT BE CH DE FR IT LI LU NL

DOCDB simple family (publication)  
**EP 0882859 A1 19981209**; **EP 0882859 B1 20020410**; AT E216016 T1 20020415; DE 29709827 U1 19970731; DE 59803690 D1 20020516

DOCDB simple family (application)  
**EP 98110326 A 19980605**; AT 98110326 T 19980605; DE 29709827 U 19970605; DE 59803690 T 19980605