

Title (en)
VARIABLE DIAMETER PULLEY

Title (de)
SCHEIBE MIT VERSTELLBAREM DURCHMESSER

Title (fr)
POULIE A DIAMETRE VARIABLE

Publication
EP 0884504 B1 20030702 (EN)

Application
EP 97906853 A 19970307

Priority

- JP 9700713 W 19970307
- JP 5192996 A 19960308
- JP 2078197 A 19970203

Abstract (en)

[origin: EP0884504A1] A variable diameter pulley comprises a pair of pulley main bodies (18, 19) connected to a rotating shaft (15), and a power transmission ring (20) interposed between the pulley main bodies. A belt (2) is passed around an outer periphery of the power transmission ring (20). The power transmission ring (20) is made eccentric relative to an axis (15a) of the rotating shaft (15) so as to be varied in its contact diameter (D). Both pulley main bodies (18, 19) are rotatable together and relatively movable in an axial direction. Both pulley main bodies (18, 19) are biased by an elastic member (22) to move toward each other. The respective pulley main bodies (18, 19) are threadedly connected to the rotating shaft (15) by a torque cam mechanism (T) composed of a pair of thread connection mechanisms, which are inversely threaded to each other. Torque for effecting rotation of the respective pulley main bodies (18, 19) relative to the rotating shaft (15) is converted into a force, which causes both pulley main bodies (18, 19) to approach each other in equal amounts of stroke. <IMAGE>

IPC 1-7
F16H 9/20; F16H 9/10; F16H 55/56

IPC 8 full level
F16H 55/56 (2006.01); **F16H 61/662** (2006.01)

CPC (source: EP US)
F16H 55/56 (2013.01 - EP US); **F16H 2061/66295** (2013.01 - EP US)

Cited by
WO2004018904A1

Designated contracting state (EPC)
DE FR GB

DOCDB simple family (publication)
EP 0884504 A1 19981216; EP 0884504 A4 20001213; EP 0884504 B1 20030702; DE 69723237 D1 20030807; DE 69723237 T2 20040527; US 6129643 A 20001010; WO 9733105 A1 19970912

DOCDB simple family (application)
EP 97906853 A 19970307; DE 69723237 T 19970307; JP 9700713 W 19970307; US 14237898 A 19980904