

Title (en)  
Running light system

Title (de)  
Laufflichtanlage

Title (fr)  
Système d'affichage à déplacement des signaux lumineux

Publication  
**EP 0886251 A3 19991117 (DE)**

Application  
**EP 98110766 A 19980612**

Priority  
DE 19726471 A 19970621

Abstract (en)  
[origin: EP0886251A2] The arrangement comprises conductor paths (A, B, C) which are connected with a voltage source and with LED elements (1 - 6), whereby a control arrangement (5) and a corresponding circuit switch the LED elements through solely the three conductor paths consecutively, to produce a running light effect. An intermittent control arrangement is used, which switches respectively one of the conductor paths off, connects another conductor path to a positive voltage, and the respectively remaining conductor path to a negative voltage.

IPC 1-7  
**G08B 5/38**

IPC 8 full level  
**G08B 5/38** (2006.01); **H05B 39/04** (2006.01); **G08B 5/36** (2006.01)

CPC (source: EP)  
**G08B 7/066** (2013.01)

Citation (search report)

- [Y] DE 4005012 A1 19910822 - JUNGBLUTH HANS JOACHIM [DE]
- [A] DE 3302981 A1 19840802 - NISSEN ADOLF ELEKTROBAU [DE]
- [A] US 4737764 A 19880412 - HARRISON JOHN M [US]
- [Y] W. RICHTER: "2 switches- 2 lamps- 1 wire", ELEKTOR, vol. 5, no. 7/8, 1979, pages 7-27, XP002115378

Designated contracting state (EPC)  
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU MC NL PT SE

DOCDB simple family (publication)  
**EP 0886251 A2 19981223; EP 0886251 A3 19991117; EP 0886251 B1 20030102**; DE 19726471 A1 19981224; DE 59806788 D1 20030206; ES 2190007 T3 20030716

DOCDB simple family (application)  
**EP 98110766 A 19980612**; DE 19726471 A 19970621; DE 59806788 T 19980612; ES 98110766 T 19980612